Coaxial Vacuum Hose Assemblies

For Dynabrade Vacuum Systems

See Page 41 for Electric Models 61300 and 61301

94941

- 1-1/4" x 20 ft.
- Includes everything as shown below.
- Air line is inside of exhaust hose for ease of use and convenience.
- Compared To The Competition:
- 2 4 ft. longer.
- 2 lbs. lighter.
- More flexible exhaust hose.
- 66% lighter airline see below on this page for specific details.
- Added features of the swivel adapter, Dynabrade's button-release coupler.



Flex-Hose Air Line

- Abrasion resistant.
- For use on air tools and spray equipment.
- Two-thirds lighter than PVC/rubber-type hose.
- 290 lbs. working pressure. 870 PSI burst strength.

3/8" Sizes

94851 • 12 ft. with male to male fittings.	94852 12 ft. with male to female fittings.
94876 • 25 ft. with male to male fittings.	94892 • 25 ft. with male to female fittings.
9485350 ft. with male to male fittings.	94854 • 50 ft. with male to female fittings.
94860 • 328 ft., bulk roll, no fittings.	94860 • Hose-by-the-foot, up to 328 ft, no fittings.

LIGHTWEIGHT, TOUGH AND HIGHLY FLEXIBLE!

Factory Installed Fittings9649796491• Male and male.• Male and female.

94852

Sanding Pad Store Counter Display Pack

- Each display pack consists of ten pads in a refillable Dynabrade display box.
- These are our premium urethane balanced random orbital sanding pads.
- All pads have a 5/16"-24 male thread.
- Fit most other brands of sanders also.

Part Number	Contents
95994	56106 – 5" Non-Vac
95995	56104 – 5" Vacuum
95996	56107 – 6" Non-Vac
95997	56105 – 6" Vacuum

