11" Random Orbital Sanders

- · Sand large areas faster than ever! Smooth and controllable.
- · Ideal for trucks, buses and emergency vehicles.
- All models include 56231 Hook-Face Pad and reversible side comfort handle.



Large 3/4" diameter random orbital action makes the difference!

Pneumatic, Non-Vacuum

Model 58480

- · Powerful 2,500 RPM, .7 hp air motor.
- · Reversible side comfort handle.
- Insulated handle.

Pneumatic, Vacuum-Ready

Model 58485

- For use with "0" style abrasive discs, which allow dust to be drawn up through pad holes.
- · For connection to external vacuum system.



Model 58480



Note: Interface Pads available on page 59.

Model Number	Motor hp	Motor RPM	Pad Dia. Inch	Maximum Air Flow CFM/SCFM	Hose I.D. Size Inch	Air Inlet Thread	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
58480	.7	2,500	11	3/27	3/8	1/4" NPT	90	8.3	17	6
58485	.7	2,500	11	3/27	3/8	1/4" NPT	90	9.1	17	6

Electric, Non-Vacuum

Model 51582

- 9 amp motor.
- 0 3,000 RPM with variable speed control desired RPM can be locked-in with speed lock button.
- · Comfort grip, three-position handle included.
- · Smooth and controllable.
- Double-insulated housing, 8 ft. flexible cord, and built-in tool rest.

1-1/4" Dia. Vac Port

Electric, Vacuum-Ready

Model 51583

- For use with "0" style abrasive discs, which allow dust to be drawn up through pad holes.
- For connection to external vacuum system.

Model Number	Motor RPM	Pad Dia. Inch	Voltage	Current	Phase	Frequency	Weight Pound	Length Inch	Height Inch
51582	0 - 3,000	11	120 V (AC)	9 Amp.	1	60 Hz	11.3	21	7-5/16
51583	0 - 3,000	11	120 V (AC)	9 Amp.	1	60 Hz	12.5	21-1/2	7-5/16