


6" & 8" Gear-Driven "Mud Hog" Sanders

- Powerful and lightweight.
- 900 RPM motor produces excellent low speed torque.
- Adjustable speed control. Soft grip housing insulates from cold.
- Our best PSA urethane, weight-mated sanding pad included for optimum performance.
- Hook pads available on page 56.



Unique cutting action is specific to "Mud Hogs" for quick and efficient filler removal.



Non-Vacuum

Model 10760

6" Diameter

- Includes 57762 PSA Pad.

Model 10763

8" Diameter

- Includes 56234 PSA Pad.



Model 10763

Central Vacuum-Ready

- Combination lip-seal overskirt allows enhanced vacuum capability and greater workpiece visibility.
- Dust is drawn away from air motor (reducing contamination) for a smoother, easier path of extraction.
- Anti-clog design is advantageous when sanding damp filler material.

Model 10761

6" Diameter

- Includes 57763 PSA Pad.
- 1-1/4" dia. vacuum port.

Model 10764

8" Diameter

- Includes 56235 PSA Pad.
- 2" dia. vacuum port.



Model 10764

**SEE PAGE 56 FOR
ORANGE SANDING PADS!**

Model Number	Motor hp	Motor RPM	Pad Dia. Inch	Maximum Air Flow CFM/SCFM	Hose I.D. Size Inch	Air Inlet Thread	Weight Pound	Length Inch	Height Inch
10760	.45	900	6	3/23	1/4	1/4" NPT	3.6	11-1/2	5-5/8
10761	.45	900	6	3/23	1/4	1/4" NPT	3.8	11-1/2	5-5/8
10763	.45	900	8	3/23	1/4	1/4" NPT	3.9	12-1/2	5-9/16
10764	.45	900	8	3/23	1/4	1/4" NPT	4.3	12-1/2	5-9/16

Additional Specifications: Air Pressure 90 PSIG