Dry Dynabug® "Model T" Sander

- The lightest tool we offer weighs only 1 pound!
- · Great finishing tool; use for color sanding.
- · Base plate is Hook-Face to accept interface pads.
- · Adjustable speed control, runs up to 20,000 RPM.
- · Uses reattachable and PSA abrasive sheets and discs.
- Never needs air tool oil.

· All models on this page include 3 ft. flexible air hose.

Up to 3/16" ORBITAL ACTION the faster the sander runs, the more aggressive the cutting action.

5" and 6" Diameter Round Models

Model 10475

5" Diameter

• Includes 56249 PSA Pad.

Model 10477

5" Diameter

 Includes 56248 Hook-Face Pad.

Model 10481

6" Diameter

Includes 56269 PSA Pad.

Model 10483

6" Diameter

 Includes 56268 Hook-Face Pad.



4" x 4-1/4" Rectangular Models

- Use 4-1/2" x 4-1/4" paper for hook or PSA pads.
- Clips are good for 9" x 11" sheet paper, cut in four, or 6" disc will fit.

Model 10470

· With clips, includes 57999 PSA Pad.

Model 10479

· Without clips, includes 56244 PSA Pad.

Model 10472

· Without clips, includes 57998 Hook-Face Pad.



· Ready for hook-up to central vac system or our portable vacuum systems. Both models have 1" diameter exhaust port for vacuum hose hook-up.

Model 10485

 Includes 56286 PSA Vacuum Pad.

Model 10487

 Includes 56285 Hook-Face Vacuum Pad.





Hook-face base plate included on all models.

Model	Motor	Orbit Dia.	Sound	Air Flow Rate	Air Inlet	Hose	Air Pressure	Weight	Length	Height
Number	RPM	Inch	Level	CFM/SCFM	Thread	Size	PSIG	Pound	Inch	Inch
All Models	20,000 max.	3/16"	83 max. dB(A)	1/9	1/4" NPT	1/4"	90	1.0	5	3