


Wet Random Orbital Sanders

- Quickly remove runs, sags, orange peel, dust nibs and other imperfections.
- Achieve a uniform and consistent finish faster and easier than before.
- Saves time and labor; increases production.
- Each model comes complete with air and water connections.
- 10,000 RPM air motor with adjustable speed control.
- Overskirt shroud is standard on all machines to control water splash.
- "Short-Nap" Hook-Face Sanding Pad included (1/2" thick).
- Hook-up to garden hose or optional 96575 Portable Wet Tank (shown below).
- Interface Pads available on page 59.




TWO-WAY WATER VALVE
Push the button as desired, or... lock the valve in place for desired water flow rate!

Wet Random Orbital Sander Models



TIGHT 3/32" ORBIT

- Provides the very best finish. Excellent finesse sander.



3/16" ORBIT

- Ideal for general wet sanding and production-type jobs.

Tool Size	3/32" Orbit Models
3-1/2"	10351
5"	10353
6"	10354

Tool Size	3/16" Orbit Models
3-1/2"	10341
5"	10343
6"	10345

Included Air and Water Connections



Optional Portable Wet Tank

Part No. 96575

- Eliminates need for garden hose.
- Two gallon capacity.
- Hand pump manually pressurizes container (50 PSI max.).
- Bring water source to the work. No need to trip over water hoses on the busy shop floor.



Model Number	Motor hp	Motor RPM	Pad Dia. Inch	Sound Level	Air Flow Rate CFM/SCFM	Air Inlet Thread	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
10341/10351	.24	10,000	3-1/2	76 dB(A)	2/16	1/4" NPT	90	2.1	6	3-3/4
10343/10353	.24	10,000	5	77 dB(A)	2/16	1/4" NPT	90	2.1	6-1/2	3-5/8
10345/10354	.24	10,000	6	74 dB(A)	2/16	1/4" NPT	90	2.2	7	3-1/2