

New Products

The Latest Innovations from Dynabrade!



3" Diameter Buffing Tools

.2 hp, Air-Powered Sander/Buffer and Rotary Buffer

FOR TERRY CLOTH,
WOOL, & FOAM BUFFS
3" diameter

For Repair of Sanding Scratches on Clearcoat



3" (76 mm) Sander/Buffer


Model 69540 12,000 RPM

- Dual-purpose tool offers random orbital sanding and rotary buffing.
- Repairs dust nibs and blemishes on paints and clear coats.
- Also used to repair hazy/cloudy headlights, and other clear/colored acrylic surfaces.
- 3" (76 mm) diameter allows use on contoured surfaces and tight areas.
- In rotary mode, offers all the benefits of model 69550 below.
- Shown with optional polishing pad.


3" (76 mm) Rotary Buffer

Model 69550 12,000 RPM

- Accepts 3" (76 mm) wool and foam buff pads.
- Runs at 12,000 RPM free-speed, then slows to under 4,000 RPM in use.
- Ideal for buffing door/window columns and posts, plus recessed areas and contoured surfaces.
- Lightweight, palm-style design offers great comfort and control.
- Adjustable speed regulator included.
- Shown with optional polishing pad.



3/16"
(5 mm)
Dia. Orbit



Rotary
Motion



Model
69540

*Switch allows
easy change
of action!*



Model
69550



Model Number	Motor hp (W)	Motor RPM	Sound Level (Sanding)	Sound Level (Buffing)	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
69540	.2 (149)	12,000	71 dB(A)	74 dB(A)	12 (334)	1/4 (6)	1/4" NPT	1.5 (.67)	6.1 (154)	3.7 (94)
69550	.2 (149)	12,000	N/A	74 dB(A)	12 (334)	1/4 (6)	1/4" NPT	1.5 (.67)	6.1 (154)	2.6 (70)

Tune-Up Kit: No. 96221 • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

DYNABRADE AUTOMOTIVE AFTERMARKET

8989 Sheridan Dr. • Clarence, NY 14031-1419 • 716-631-0100 • F: 716-631-2073 • E: autoaft@dynabrade.com • dynabradeauto.com