

DYNABRADE AUTOMOTIVE AFTERMARKET**PRODUCT SPOTLIGHT****AutoFile II Belt Tool****For Easy, Efficient Removal of Spot Welds!****7° Offset Handle Design
for Ergonomic Comfort!**

- Includes four Norton SG Blaze Abrasive Belts, 1/2" wide x 18" long! *60 grit (2), 80 grit, 120 grit*
- Non-Woven Nylon Belts also available!

*AutobradeRed***The Most Versatile Shop Tool Around!**





- **Ideal for grinding sharp metal edges, rusted bolts and welds.**
- **Also great for blending and scuffing on grooves and contours.**
- **Grinding head pivots 360°. Excellent in tight areas!**

**SEE the Auto File II
at Work!**

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (L/Min)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Air Pressure PSIG	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
18100	.5 (373)	20,000	79 dB(A)	22 (623)	3/8 (10)	1/4" NPT	90	2.8 (1.3)	15 (381)	5 (127)

Optional Contact Arm Assemblies

All rubber Contact Wheels are 70 durometer, unless noted.

Part Number	Comments	Belt Size (W x L)	Replacement Contact Wheel Assembly (includes bearing and shaft)
11203 Order 11312 for heavy-duty version 	<ul style="list-style-type: none"> • Included with 18100 • Grind over contact wheel or platen 	1/2" x 18"	11078 5/8" dia. x 3/8" wide, steel
11204 	<ul style="list-style-type: none"> • Unique offset design • Strap polishing is easy with this arm 	1/8", 1/4" or 1/2" x 18"	11204: 11080 Wheel, 1" dia. x 3/8" wide 11305: 11093 Wheel, 1" dia. x 3/8" wide, 40 duro (Both wheels radiused rubber)

See Reverse Side for More Contact Arm Assemblies!

Optional Contact Arm Assemblies

All rubber Contact Wheels are 70 durometer.

Part Number	Comments	Belt Size (W x L)	Replacement Contact Wheel Assembly (includes bearing and shaft)
11201 	<ul style="list-style-type: none"> • 45 PSIG maximum • Enter channels as small as 7/16" 	1/2" x 18"	11068 5/16" dia. x 3/8" wide, steel
11202 	<ul style="list-style-type: none"> • Enter 5/16" x 3/4" openings 	1/4" x 18"	11074 5/8" dia. x 1/8" wide, rubber
11206 Order 11326 for heavy-duty version 	<ul style="list-style-type: none"> • Utilize 3/4" belts 	5/8" or 3/4" x 18"	11282 3/4" dia. x 5/8" wide, rubber
11280 	<ul style="list-style-type: none"> • Grind corners, enter grooves, strap polish • "V" shape wheel 	1/8" or 1/4" x 18"	11086 1" dia. x 3/8" wide, urethane, tapered
11304 "The Banana Arm" 	<ul style="list-style-type: none"> • Work on broad areas; levels in-line scratch; blend stainless 	1/2" x 18"	11078 5/8" dia. x 3/8" wide, rubber
11312 	<ul style="list-style-type: none"> • Heavy-duty steel • Grind over contact wheel or platen 	1/2" x 18"	11078 5/8" dia. x 3/8" wide, rubber
11314 	<ul style="list-style-type: none"> • 45 PSIG maximum • File round openings as small as 7/16" 	1/4" x 18"	11066 5/16" dia. x 1/8" wide, steel
11320 Offset Arm 	<ul style="list-style-type: none"> • For flat grinding using platen at or near corners and edges of large radius round • Contact wheel is offset to prevent gouging 	1/2" x 18"	11078 5/8" dia. x 3/8" wide, rubber
11321 	<ul style="list-style-type: none"> • 45 PSIG maximum • Work on contact wheel or platen pad 	1/2" x 18"	11070 7/16" dia. x 3/8" wide, rubber
11325 	<ul style="list-style-type: none"> • For flat grinding and heavy stock removal 	1/2" x 18"	11078 5/8" dia. x 3/8" wide, rubber



DYNABRADE AUTOMOTIVE AFTERMARKET

8989 Sheridan Drive • Clarence, NY 14031-1490 • 716-631-0100 • Fax: 716-631-2073
Email: autoaft@dynabrade.com • DynabradeAuto.com

