



Two-Hand Dynorbital® Supreme

Air Powered Series of Long Handle Random Orbital Sanders

Long handle allows two-hand support of tool.
Better reach and comfort, especially in vertical positions.

ABRASIVE CAPACITY

- 5" (127 mm) and 6" (152 mm) diameter discs.

Non-Vacuum

MODEL 57200

5" (127 mm) Diameter
3/16" Dia. Orbit

- Includes 56106 Disc Pad.

MODEL 59200

5" (127 mm) Diameter
3/8" Dia. Orbit

- Includes 56106 Disc Pad.

MODEL 57210

6" (152 mm) Diameter
3/16" Dia. Orbit

- Includes 56107 Disc Pad.

MODEL 59210

6" (152 mm) Diameter
3/8" Dia. Orbit

- Includes 56107 Disc Pad.



Model
57210

NEW
3/8" Dia. Orbit Models
for More Aggressive
Sanding Action!

Self-Generated Vac-Ready

- Connects to optional self-contained collection systems.

MODEL 57201

5" (127 mm) Diameter
3/16" Dia. Orbit

- Includes 56104 Disc Pad.

MODEL 59201

5" (127 mm) Diameter
3/8" Dia. Orbit

- Includes 56104 Disc Pad.

MODEL 57211

6" (152 mm) Diameter
3/16" Dia. Orbit

- Includes 56105 Disc Pad.

MODEL 59211

6" (152 mm) Diameter
3/8" Dia. Orbit

- Includes 56105 Disc Pad.



Model
57201

Basic Self-Generated Vacuum

- Includes self-generated vac-ready tool with low profile premium urethane weight-mated sanding pad and 50617 Self-Contained Dust Collection System featuring 6' (183 cm) long vacuum exhaust hose assembly with 50683 Standard Reusable Felt Bag.

MODEL 57202

5" (127 mm) Diameter
3/16" Dia. Orbit

- Includes 56104 Disc Pad.

MODEL 57212

6" (152 mm) Diameter
3/16" Dia. Orbit

- Includes 56105 Disc Pad.




Model
57202

3/8" Dia. Orbit
For Aggressive
Sanding



3/16" Dia. Orbit
For General
Sanding



Deluxe Self-Generated Vacuum

- Includes self-generated vac-ready tool with low profile premium urethane weight-mated sanding pad and 54290 "Bag-in-Box" portable self-contained dust collection system featuring 6' long vacuum exhaust hose assembly, 95361 Air Line and disposable paper dust bag inside a durable outer case (case also used to store tool).

MODEL 57203

5" (127 mm) Diameter
3/16" Dia. Orbit

- Includes 56104 Disc Pad.

MODEL 57213

6" (152 mm) Diameter
3/16" Dia. Orbit

- Includes 56105 Disc Pad.

Model
57203



Central Vac-Ready

- Connects to optional central vacuum system.

MODEL 57204

5" (127 mm) Diameter
3/16" Dia. Orbit

- Includes 56104 Disc Pad.

MODEL 57214

6" (152 mm) Diameter
3/16" Dia. Orbit

- Includes 56105 Disc Pad.

Two-Hand Dynorbital® Supreme

Air Powered Series of Long Handle Random Orbital Sanders



Model Number	Motor HP (W)	Motor RPM	Pad Dia. Inch (mm)	Sound Level	Air Flow Rate CFM/SCFM (LPM)	Air Pressure PSIG (Bars)	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57200	.4 (298)	12,000	5 (127)	78 dB(A)	4/27 (765)	90 (6.2)	2.7 (1.2)	10-1/4 (260)	4-1/2 (114)
59200	.4 (298)	12,000	5 (127)	78 dB(A)	4/27 (765)	90 (6.2)	2.7 (1.2)	10-1/4 (260)	4-1/2 (114)
57201	.4 (298)	12,000	5 (127)	82 dB(A)	4/27 (765)	90 (6.2)	2.7 (1.2)	10-1/4 (260)	4-1/2 (114)
59201	.4 (298)	12,000	5 (127)	82 dB(A)	4/27 (765)	90 (6.2)	2.7 (1.2)	10-1/4 (260)	4-1/2 (114)
57204	.4 (298)	12,000	5 (127)	86 dB(A)	4/27 (765)	90 (6.2)	2.7 (1.2)	10-1/4 (260)	4-1/2 (114)
57210	.4 (298)	12,000	6 (152)	82 dB(A)	4/27 (765)	90 (6.2)	4.5 (2.0)	10-1/2 (267)	4-1/2 (114)
59210	.4 (298)	12,000	6 (152)	82 dB(A)	4/27 (765)	90 (6.2)	4.5 (2.0)	10-1/2 (267)	4-1/2 (114)
57211	.4 (298)	12,000	6 (152)	88 dB(A)	4/27 (765)	90 (6.2)	4.5 (2.0)	10-1/2 (267)	4-1/2 (114)
59211	.4 (298)	12,000	6 (152)	88 dB(A)	4/27 (765)	90 (6.2)	4.5 (2.0)	10-1/2 (267)	4-1/2 (114)
57214	.4 (298)	12,000	6 (152)	84 dB(A)	4/27 (765)	90 (6.2)	4.5 (2.0)	10-1/2 (267)	4-1/2 (114)

Additional Specifications: Orbit Diameter 3/16" (5 mm) • Spindle Thread 5/16"-24 Female • Air Inlet Thread 1/4" NPT • Hose Size 1/4" (6 mm)
 Recommended Air Line Accessory: For Best Performance use 95676 Coupler/Plug Assembly

PORTABLE VACUUM SYSTEMS

Dustless Vacuum Systems and Accessories

Ideal for use with all Dynabrade Central Vacuum Air Tools! Compatible with other brands of air and electric tools.

- Meets and exceeds OSHA requirements for noise level output, 58 dB(A).
- Increases productivity, safer work place where audible communication is required.
- Auto start/stop: controls vacuum motor start/stop on demand from hand tool lever.
- Designed to operate up to four air tools and one electric tool independently or simultaneously for maximum use of vacuum system.
- Complete vacuum system fully grounded, suction hose and connectors are manufactured from conductive materials to eliminate static electric build up.
- Provides high air flow, 120 SCFM (3,398 LPM), and vacuum, 90" (229 cm) of water lift, for a wide range of cleaning applications.
- Efficient, cleanable and replaceable air filter element.
- 64609 H.E.P.A. Filter Kit (.3 micron capacity) is available.
- Rheostat motor control allows for variable vacuum suction.
- Offset inlet fitting provides even filling of canister and disperses debris away from filter element.



Model 64600
10-Gallon (37.8 liter) System
 Shown with standard and optional accessories.

MODEL 64600

10-Gallon (37.8 liter) System

- One-to-two tool operation.
- Includes each of the following:
 - (1) 64601 Filter Bag (10-gallon).
 - (1) 64602 Filter Element.
 - (1) 64603 Air Line/Vacuum Hose Assembly.
 - (1) 95894 Hose Cuff.

Other vacuum models available.



DYNABRADE, INC.
 8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2073
 US Consumers Call Toll Free: 1-800-828-7333

DYNABRADE INTERNATIONAL
 8989 Sheridan Drive • Clarence, New York 14031-1490 • Phone: (716) 631-0100 • Fax: 716-631-2524
 Canadian Consumers Call Toll Free: 1-800-344-1488

DYNABRADE EUROPE S.à.r.l.
 Zone Artisanale • L-5485 Wormeldange—Haut, Luxembourg • Telephone: 352 76 84 94 1 • Fax: 352 76 84 95 1

DISTRIBUTED BY: