

DYNABRADE STATIONARY EQUIPMENT

Reorder No. D06.10

Downdraft Sanding Tables

ELIMINATE AIRBORNE DUST AND CONTAMINANTS WHILE SANDING

Standard Duty Tables

64201

Working Area of
33" W x 41" L

64699

Working Area of
33" W x 60" L

64700

Working Area of
36" W x 72" L

- Ideal for use with vacuum-ready or non-vacuum tools.
- Dual filtration – accepts 1-micron pleated paper filters, 20" W x 25" L. (Models 64201 and 64699 include two filters; model 64700 includes three.)
- Each model includes one pre-filter blanket.
- Rhino Linings® coated tabletop surface is durable and anti-slip.
- 5" diameter casters allow easy maneuverability of table.
- Two handy storage compartments for tools and accessories.
- Two convenient dust-tight electric outlets.

Specifications

- **Power Source:** One heavy duty electric motor, 1.0 hp
- **Electric Capacity:** 110 volt, 220 volt (single phase). Three phase available upon request.
- **Two Paper Filter Sizes Available:** 64671: 20" wide x 25" long x 2" thick standard paper air filter; 64672: 20" wide x 25" long x 2" thick UL rated class I non-flammable air filter (recommended when sanding bare metal).



Heavy Duty Table

64657 Working Area of 48" W x 96" L

- Includes eight 20" x 25" paper filters (64658) and four 16" x 25" paper filters (64659).
- Dual filtration – pre-filter blanket and 1-micron paper filters.
- Up to 70% more filter area than competitive brands.
- High quality reverse incline blowers. Heavy duty TEFC twin electric motors.
- Base unit is all-metal construction with CNC milled 3/4" MDF tabletop.
- Optional anti-static and anti-slip mat available (64970) as well as optional 5" diameter casters.

Specifications

- **Power Source:** Two heavy duty TEFC electric motors, 1.5 hp
- **Electric Capacity:** 115 volt (single phase). 208 volt (three phase), 230 volt (single phase), 230 volt (three phase), 460 volt (three phase) available upon request.



Model Number	Motor hp	Volts	Phase	Vacuum Suction	Sound Level	Working Area Width	Working Area Length	Height Inch (mm)	Shipping Weight
64201	1	110/220	1	3,000 CFM	72 dB(A)	33" (838 mm)	41" (1,041 mm)	36 (914)	275 lbs.
64657	1.5 (Dual)	115	1	7,000 CFM	75 dB(A)	48" (1,219 mm)	96" (2,438 mm)	37 (940)	970 lbs.
64699	1	110/220	1	3,000 CFM	72 dB(A)	33" (838 mm)	60" (1,524 mm)	36 (914)	285 lbs.
64700	1	110/220	1	3,000 CFM	72 dB(A)	36" (914 mm)	72" (1,829 mm)	36 (914)	365 lbs.



For additional Dynabrade tools and accessories, see reverse side.

Additional Dust Collection Solutions from Dynabrade

Electric Portable Vacuum Systems

61300

9.9 Gallon Capacity

- Heavy duty stainless steel drum; variable vacuum control.
- HEPA filtration (0.3 micron) with felt insert and paper bag.
- Electronic thermal protection device prevents heat overload of motor.
- Heavy duty four-wheel trolley with easy tilt 'n clean drum. Drum can be removed for use in special applications or locations.
- Two of the most innovative, lightweight 1-1/4" dia. x 20' long coaxial hoses on the market today. Auto on/off switch, 27' electrical cord.

61301

17 Gallon Capacity



HEPA filtration
(0.3 micron)

**Connect and
Operate Two
Tools at Once!**



Air Powered Palm-Style Random Orbital Sanders

Self-Generated Vacuum

- Connect to portable self-contained dust collection systems, available separately from Dynabrade.
- Includes low profile, premium urethane, weight-mated sanding pad.

Central Vacuum

- 1" diameter vacuum port for easy central vacuum connection.
- Includes low profile, premium urethane, weight-mated sanding pad.



59023
Dynorbital-Spirit®



56818
Dynorbital-Supreme

Dynorbital-Spirit® Models

Pad Diameter	3/8" Orbit Model (Pad)	3/16" Orbit Model (Pad)	3/32" Orbit Model (Pad)
3" (76 mm)	59103 (56084)	59108 (56084)	59113 (56084)
3-1/2" (89 mm)	59003 (56098)	59018 (56098)	59033 (56098)
5" (127 mm)	59008 (56104)	59023 (56104)	59038 (56104)
6" (152 mm)	59013 (56105)	59028 (56105)	59043 (56105)

Dynorbital® Supreme Models

Pad Diameter	3/16" Orbit Model (Pad)	3/32" Orbit Model (Pad)
3-1/2" (89 mm)	56803 (56098)	56843 (56098)
5" (127 mm)	56818 (56104)	56853 (56104)
6" (152 mm)	56829 (56105)	56862 (56105)



59024
Dynorbital-Spirit®



56819
Dynorbital-Supreme

Dynorbital-Spirit® Models

Pad Diameter	3/8" Orbit Model (Pad)	3/16" Orbit Model (Pad)	3/32" Orbit Model (Pad)
3" (76 mm)	59104 (56084)	59109 (56084)	59114 (56084)
3-1/2" (89 mm)	59004 (56098)	59019 (56098)	59034 (56098)
5" (127 mm)	59009 (56104)	59024 (56104)	59039 (56104)
6" (152 mm)	59014 (56105)	59029 (56105)	59044 (56105)

Dynorbital® Supreme Models

Pad Diameter	3/16" Orbit Model (Pad)	3/32" Orbit Model (Pad)
3-1/2" (89 mm)	56804 (56098)	56844 (56098)
5" (127 mm)	56819 (56104)	56854 (56104)
6" (152 mm)	56830 (56105)	56863 (56105)

Channel Vacuum Sanding Pads

- Channel Vacuum Pads have 1/8" deep recessed channel, so there is no need to align the abrasive holes to pad holes!
- Premium urethane pads resist heat build-up and are perfectly weight-mated for use with Dynabrade models.
- 5/16"-24 male thread; 13,000 RPM maximum operating speed.



56251

Vinyl-Face (PSA)

Part No.	Dia.	Thickness	Density
56251	5"	3/8"	Soft
56252	5"	3/8"	Medium
56254	5"	5/8"	Medium
56256	5"	5/8"	Soft
56261	6"	3/8"	Soft
56262	6"	3/8"	Medium
56264	6"	5/8"	Medium
56266	6"	5/8"	Soft

Hook-Face

Part No.	Dia.	Thickness	Density
56250	5"	3/8"	Medium
56253	5"	3/8"	Soft
56255	5"	5/8"	Medium
56257	5"	5/8"	Soft
56260	6"	3/8"	Medium
56263	6"	3/8"	Soft
56265	6"	5/8"	Medium
56267	6"	5/8"	Soft

Visit our Website for more Tools and Related Accessories

www.dynabrade.com



DYNABRADE, INC.

8989 Sheridan Drive, Clarence, New York 14031-1490
Phone: (716) 631-0100 • Fax: 716-631-2073

US Consumers Call Toll Free: 1-800-828-7333

©DYNABRADE, INC., 2006

PRINTED IN U.S.A.

2/06

DISTRIBUTED BY:

