

.5 hp Die Grinders

7° Offset, Short Shank, Gearless, Front Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

- Gearless for reduced maintenance and downtime.

Model 52211

18,000 RPM, 1/4" Collet

Model 52261

18,000 RPM, 6 mm Collet

Model 52212

20,000 RPM, 1/4" Collet

Model 52262

20,000 RPM, 6 mm Collet

Model 52213

24,000 RPM, 1/4" Collet

Model 52263

24,000 RPM, 6 mm Collet



Model 52211



Gearless

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52211 / 52261	.5 (373)	18,000	77 dB(A)	28 (793)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	4-1/2 (114)
52212 / 52262	.5 (373)	20,000	77 dB(A)	28 (793)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	4-1/2 (114)
52213 / 52263	.5 (373)	24,000	82 dB(A)	28 (793)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	4-1/2 (114)

Tune-Up Kit: No. 96044 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

.5 hp Die Grinders

7° Offset, Short Shank, Gearless, Rear Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

- Gearless for reduced maintenance and downtime.
- Extended rear exhaust muffler design.

Model 52221

18,000 RPM, 1/4" Collet

Model 52223

24,000 RPM, 1/4" Collet

Model 52222


20,000 RPM, 1/4" Collet



Model 52221



Gearless



Dynaswivel® air line connector is ideal for use with most air tools. The Dynaswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52221	.5 (373)	18,000	77 dB(A)	23 (651)	3/8 (10)	1/4" NPT	—	2.0 (0.9)	8-1/8 (206)	4-1/2 (114)
52222	.5 (373)	20,000	79 dB(A)	25 (708)	3/8 (10)	1/4" NPT	—	2.0 (0.9)	8-1/8 (206)	4-1/2 (114)
52223	.5 (373)	24,000	78 dB(A)	27 (765)	3/8 (10)	1/4" NPT	—	2.0 (0.9)	8-1/8 (206)	4-1/2 (114)

Tune-Up Kit: No. 96044 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Collet Inserts: Page 94 • Carbide Burrs: Page 189 • Accessories: Page 159