

.7 hp Die Grinders

Straight-Line, Front Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

Model 52256

15,000 RPM, 1/4" Collet

Model 52257

18,000 RPM, 1/4" Collet

Model 52258

20,000 RPM, 1/4" Collet

Model 52264

15,000 RPM, 6 mm Collet

Model 52265

18,000 RPM, 6 mm Collet

Model 52256



Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52256 / 52264	.7 (522)	15,000	83 dB(A)	31 (878)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	1-7/8 (48)
52257 / 52265	.7 (522)	18,000	87 dB(A)	33 (935)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	1-7/8 (48)
52258 / —	.7 (522)	20,000	91 dB(A)	34 (963)	3/8 (10)	1/4" NPT	—	1.7 (0.8)	6 (152)	1-7/8 (48)

Tune-Up Kit: No. 96529 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

.7 hp Die Grinders

Straight-Line, Rear Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

- Extended rear exhaust muffler design.

Model 52100

950 RPM, 1/4" Collet

Model 52101

3,400 RPM, 1/4" Collet

Model 52102

4,500 RPM, 1/4" Collet

Model 52276

15,000 RPM, 1/4" Collet

Model 52277

18,000 RPM, 1/4" Collet

Model 52278

20,000 RPM, 1/4" Collet

Model 52103

950 RPM, 6 mm Collet

Model 52104

3,400 RPM, 6 mm Collet

Model 52105

4,500 RPM, 6 mm Collet

Model 52281

15,000 RPM, 6 mm Collet

Model 52282

18,000 RPM, 6 mm Collet

Model 52283

20,000 RPM, 6 mm Collet

Model 52276



Motor Tune-Up Kits will extend the life of an air tool when used with a preventative maintenance schedule.

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52100 / 52103	.7 (522)	950	84 dB(A)	34 (957)	3/8 (10)	1/4" NPT	1/2"-20 Male	3.6 (1.6)	12-1/2 (318)	1-7/8 (48)
52101 / 52104	.7 (522)	3,400	82 dB(A)	35 (977)	3/8 (10)	1/4" NPT	1/2"-20 Male	2.7 (1.2)	9-1/2 (241)	1-7/8 (48)
52102 / 52105	.7 (522)	4,500	82 dB(A)	35 (977)	3/8 (10)	1/4" NPT	1/2"-20 Male	2.7 (1.2)	9-1/2 (241)	1-7/8 (48)
52276 / 52281	.7 (522)	15,000	80 dB(A)	32 (906)	3/8 (10)	1/4" NPT	—	2.3 (0.7)	8-1/8 (206)	1-7/8 (48)
52277 / 52282	.7 (522)	18,000	81 dB(A)	34 (963)	3/8 (10)	1/4" NPT	—	2.3 (0.7)	8-1/8 (206)	1-7/8 (48)
52278 / 52283	.7 (522)	20,000	81 dB(A)	37 (1,048)	3/8 (10)	1/4" NPT	—	2.3 (0.7)	8-1/8 (206)	1-7/8 (48)

Tune-Up Kit: No. 96529 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Collet Inserts: Page 94 • Carbide Burrs: Page 189 • Accessories: Page 159