

2" Dia. Disc Sanders

.33 hp and .4 hp Models

ABRASIVE
CAPACITY

ABRASIVE DISCS

2" (51 mm) and 3" (76 mm)
diameter

High Quality Air-Powered Disc Sanders

Right Angle, .33 hp, Gearless, Rear Exhaust

Model 52590 18,000 RPM

- Includes 51345 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter disc pads, sold separately.
- Features standard muffler for more compact design.
- Tool combines top efficiency with great value.



Model 52590



Motor Tune-Up Kits can extend the life of a tool, when used as part of a regular preventative maintenance schedule. (See page 192.)



Gearless

Important: Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52590	.33 (246)	18,000	81 dB(A)	20 (567)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.9 (0.8)	4-1/2 (114)	3-7/8 (98)

Tune-Up Kit: No. 96505 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Right Angle, .4 hp, Front Exhaust

- Includes 51344 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter pads, sold separately.
- Optional safety-lock lever available.



Model 51822



Dynaswivel® air line connector is ideal for use with most air tools. The Dynaswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)

Model 51820 12,000 RPM

Model 51821 15,000 RPM

Model 51822 20,000 RPM

Important: Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51820	.4 (298)	12,000	85 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)
51821	.4 (298)	15,000	84 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)
51822	.4 (298)	20,000	87 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)

Tune-Up Kit: No. 96179 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Right Angle, .4 hp, Rear Exhaust

- Includes 51344 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter pads, sold separately.

Model 52520

12,000 RPM, Extended Muffler

Model 52521

15,000 RPM, Extended Muffler

Model 52522

20,000 RPM, Extended Muffler

Model 52540

12,000 RPM, Standard Muffler

Model 52541

15,000 RPM, Standard Muffler

Model 52542

20,000 RPM, Standard Muffler



Model 52520

Model 52520 Disc Sander offers efficient weld removal.

Important: Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52520	.4 (298)	12,000	85 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52521	.4 (298)	15,000	83 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52522	.4 (298)	20,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52540	.4 (298)	12,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)
52541	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)
52542	.4 (298)	20,000	87 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)

Tune-Up Kit: No. 96179 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK