

4-1/2"-5" Dia. Disc Sanders

1.2 hp Models

ABRASIVE CAPACITY
ABRASIVE DISCS
 4-1/2" (114 mm) to
 5" (127 mm) diameter

High Quality Air-Powered Disc Sanders

Vertical, 1.2 hp, Side Exhaust

- Each model Includes 51150 Disc Pad Assembly (5" diameter).
- Powerful air motor is governor-controlled to maintain RPM under heavy load.
- Safety-lock throttle lever prevents accidental start-up.
- Side handle increases control and reduces hand fatigue.
- For best performance use 98273 Coupler and Plug Assembly.

Model 50304 8,500 RPM

Model 50307 11,000 RPM



Model 50307



95462 Dynaswivel® air line connector is ideal for use with these tools. Dynaswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
50304	1.2 (895)	8,500	75 dB(A)	32 (906)	1/2 (13)	1/2" NPT	5/8"-11 Male	4.0 (1.8)	8 (203)	6 (152)
50307	1.2 (895)	11,000	78 dB(A)	36 (1,020)	1/2 (13)	1/2" NPT	5/8"-11 Male	4.0 (1.8)	8 (203)	6 (152)

Tune-Up Kit: No. 96011 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Right Angle, 1.2 hp, Rear Exhaust

- Each model includes 51150 Disc Pad Assembly (5" diameter).
- Powerful air motor is governor-controlled to maintain RPM under heavy load.
- Lubricated gears increase durability.
- Reversible side handle increases control and reduces fatigue.
- Safety-lock throttle lever prevents accidental start-up.
- NOTE: For maximum performance, optional 95870 air hose (1/2" dia.) is recommended.

Model 50345 8,500 RPM

Model 50360 12,000 RPM



Model 50345



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs. (See page 162.)



Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
50345	1.2 (895)	8,500	76 dB(A)	43 (1,218)	1/2 (13)	1/2" NPT	5/8"-11 Male	4.8 (2.2)	11-3/4 (298)	3-1/8 (80)
50360	1.2 (895)	12,000	82 dB(A)	41 (1,161)	1/2 (13)	1/2" NPT	5/8"-11 Male	4.8 (2.2)	11-3/4 (298)	3-1/8 (80)

Tune-Up Kit: No. 96011 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

