

Depressed Center Wheel Grinders

Air-Powered Grinders, 2" and 3" Diameter

ABRASIVE
CAPACITY
**TYPE 27 REINFORCED
DEPRESSED CTR. WHEELS**
2", 3" Dia. (51 mm, 76 mm)

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

2" Diameter, Right Angle, .4 hp, Rear Exhaust

- Each model includes 90999 Depressed Center Wheel (24 grit), 2" diameter with 3/8" center hole. Guard and wheel flange set also included.
- Compact, short muffler design.
- Optional 01462 Safety-Lock Throttle is available.

Model 52710 12,000 RPM
Model 52711 15,000 RPM
Model 52712 20,000 RPM


Model 52710

3" Diameter, Right Angle, .55 hp, Rear Exhaust

Model 57127 15,000 RPM

- Accepts optional 3" diameter Type 27 Depressed Center Wheel, with 3/8" center hole (wheel width of 1/8" to 1/4").
- Powerful high-torque grinding action; standard muffler for reduced sound levels.
- Gearless design for reduced maintenance and downtime.
- Removable side handle. Also includes safety-lock throttle lever, plus guard and wheel flange set.



Gearless



Model 57127

Wheel Sold Separately

3" Diameter, 7° Offset, .7 hp, Front Exhaust

Model 52700 18,000 RPM

- Accepts optional 3" diameter Type 27 Depressed Center Wheels, with 3/8" center hole (wheel width of 1/8" to 1/4").
- Powerful high-torque grinding action.
- Gearless design for reduced maintenance and downtime.
- Handle is offset 7° for enhanced operator comfort.
- Removable side handle; guard and wheel flange set included.
- Easily converts to 1/4" Die Grinder (with optional 50010 Collet), or Drill (with optional 53032 Chuck).



Use ONLY Type 27 Reinforced Depressed Center Wheels (sold separately, unless noted) with these models.



Model 52700

Wheel Sold Separately



Gearless

Important: Speed of tool must not exceed maximum operating speed of accessory. Never mount bonded grinding wheels. Always wear eye, face & body protection.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52700	.7 (522)	18,000	86 dB(A)	32 (906)	3/8 (10)	1/4" NPT	3/8"-24 Male	2.2 (1.0)	7-1/4 (184)	4-1/2 (114)
52710	.4 (298)	12,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	3 (76)
52711	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	3 (76)
52712	.4 (298)	20,000	87 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	3 (76)
57127	.55 (410)	15,000	83 dB(A)	33 (934)	3/8 (10)	1/4" NPT	3/8"-24 Male	1.9 (.8)	6 (152)	3-7/8 (98)

Tune-Up Kits: 2" Diameter Models - **96179**; 52700 - **96045**; 57127 - **96522** (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)


FASTTRACK

Depressed Center Wheels: Page 222 • Accessories: Page 159