

Cone or Plug Wheel Grinders

Air-Powered Grinders

ABRASIVE
CAPACITYCONE OR PLUG WHEELS
1-1/4" (32 mm) Diameter

Clean Metal, Grind and Smooth Weld Seams, Remove Imperfections Prior to Painting

Straight Line, 1 hp, Rear Exhaust

- Each model accepts optional Abrasive Cone or Plug Wheel, 1-1/4" diameter.
- Governor-controlled motor maintains RPM under heavy load.
- Safety-lock lever is included on all models.
- Industrial applications in fabrication plants, welding shops, foundries, steel mills and shipyards.

Model 52715 12,000 RPM

Model 52716 15,000 RPM

Model 52717 18,000 RPM

Model 52718 20,000 RPM



Model 52715

Plug Wheel Sold Separately

Straight Line, 1 hp, Rear Exhaust, 6" Extension

- Each model accepts optional Abrasive Cone or Plug Wheel, 1-1/4" diameter.
- Governor-controlled motor maintains RPM under heavy load.
- Safety-lock lever is included on all models.
- Standard cushioned grip enhances operator comfort and offers additional control.
- Industrial applications in fabrication plants, welding shops, foundries, steel mills and shipyards.

Model 52719 12,000 RPM

Model 52720 15,000 RPM

Model 52721 18,000 RPM

Model 52722 20,000 RPM



Model 52719

Plug
Wheel Sold
Separately

Model 52719



All models can be converted to 5/8"-11 thread with 53652 cone or plug adapter.

Important: Speed of tool must not exceed maximum operating speed of accessory. Never mount bonded grinding wheels. Always wear eye, face & body protection.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52715	1 (744)	12,000	82 dB(A)	38 (1,076)	3/8" NPT	3/8 (10)	3/8"-24 Male	2.0 (.9)	7-3/4 (198)	1-7/8 (48)
52716	1 (744)	15,000	80 dB(A)	39 (1,104)	3/8" NPT	3/8 (10)	3/8"-24 Male	2.0 (.9)	8-7/8 (225)	1-7/8 (48)
52717	1 (744)	18,000	81 dB(A)	40 (1,133)	3/8" NPT	3/8 (10)	3/8"-24 Male	2.0 (.9)	8-7/8 (225)	1-7/8 (48)
52718	1 (744)	20,000	80 dB(A)	44 (1,256)	3/8" NPT	3/8 (10)	3/8"-24 Male	2.0 (.9)	8-7/8 (225)	1-7/8 (48)
52719	1 (744)	12,000	82 dB(A)	38 (1,076)	3/8" NPT	3/8 (10)	3/8"-24 Male	3.3 (1.5)	13-1/4 (335)	1-7/8 (48)
52720	1 (744)	15,000	80 dB(A)	39 (1,104)	3/8" NPT	3/8 (10)	3/8"-24 Male	3.3 (1.5)	14-3/8 (365)	1-7/8 (48)
52721	1 (744)	18,000	81 dB(A)	40 (1,133)	3/8" NPT	3/8 (10)	3/8"-24 Male	3.3 (1.5)	14-3/8 (365)	1-7/8 (48)
52722	1 (744)	20,000	80 dB(A)	44 (1,256)	3/8" NPT	3/8 (10)	3/8"-24 Male	3.3 (1.5)	14-3/8 (365)	1-7/8 (48)

Tune-Up Kit: No. 96532 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Accessories: Page 159