

# Drills

## Air-Powered Drills, 1/4" Chuck

ABRASIVE  
CAPACITY

### DRILL BITS & ACCESSORIES

1/4" (6 mm) dia. maximum

### Industrial-Quality Drills in a Variety of Configurations

#### Straight Line, .4 hp, Rear Exhaust

- Each model includes 1/4" drill chuck and key.
- Extended muffler design for reduced sound levels.

**Model 53077** 950 RPM

**Model 53078** 3,200 RPM

**Model 53079** 5,000 RPM

Model 53077



13141  
Handle/Collar Assembly  
Sold Separately

#### 7° Offset, .4 hp, Rear Exhaust

- Each model includes 1/4" drill chuck and key.
- Extended muffler design for reduced sound levels.

**Model 53072** 950 RPM

**Model 53073** 3,200 RPM

**Model 53074** 5,000 RPM

Model 53072



Motor Tune-Up Kits  
will extend the life of  
an air tool when used  
as part of a preventative  
maintenance schedule.  
(See page 192.)

#### Right Angle, .4 hp, Front Exhaust

- Each model includes 1/4" drill chuck and key.

**Model 51846** 12,000 RPM

**Model 51847** 15,000 RPM

**Model 51848** 20,000 RPM

#### Right Angle, .4 hp, Rear Exhaust

- Each model includes 1/4" chuck and key.
- Standard muffler design.

**Model 53046** 12,000 RPM

**Model 53047** 15,000 RPM

**Model 53048** 20,000 RPM



Model 53046

#### Straight Line, .5 hp, Front Exhaust

**Model 53037** 20,000 RPM

- Includes 1/4" drill chuck and key.



Model 53037

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51846	.4 (298)	12,000	85 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (0.5)	5-1/2 (140)	4 (101)
51847	.4 (298)	15,000	84 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (0.5)	5-1/2 (140)	4 (101)
51848	.4 (298)	20,000	89 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (0.5)	5-1/2 (140)	4 (101)
53037	.5 (373)	20,000	87 dB(A)	27 (765)	3/8 (10)	1/4" NPT	3/8"-24 Male	1.5 (.7)	7 (178)	1-3/4 (44)
53046	.4 (298)	12,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	4 (101)
53047	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	4 (101)
53048	.4 (298)	20,000	87 dB(A)	21 (595)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.1 (.5)	5-3/4 (146)	4 (101)
53072	.4 (298)	950	79 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	2.2 (1.0)	8 (203)	6-3/4 (171)
53073	.4 (298)	3,200	80 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	2.1 (0.9)	8 (203)	5-1/2 (141)
53074	.4 (298)	5,000	78 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	2.1 (0.9)	8 (203)	5-1/2 (141)
53077	.4 (298)	950	82 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (.8)	10-1/2 (267)	1-5/8 (40)
53078	.4 (298)	3,200	81 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (.8)	10-1/2 (267)	1-5/8 (40)
53079	.4 (298)	5,000	84 dB(A)	22 (623)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (.8)	10-1/2 (267)	1-5/8 (40)

**Tune-Up Kits:** 51846-51848, 53046-53048 - **No. 96179**; 53037 - **No. 95600**; 53072-53074 - **No. 96174**; 53077-53079 - **No. 96173** (page 192)

Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



**FASTTRACK**

Accessories: Page 159