

# Versatility Grinder

## Electric Abrasive Belt Machine

ABRASIVE  
CAPACITY

### ABRASIVE BELTS

1/4-2" wide x 72" long  
(6 mm - 51 mm x 1,829 mm)

### Ideal for an Extensive Variety of Finishing Applications

- Versatility Grinder powers 72" abrasive belts in widths from 1/4" to 2", to provide a wide variety of finishing solutions.
- Ideal for use on castings and forgings, turbine blades, medical implants, investment castings and more.
- Sleek, compact design for easy space-saving set up.
- Combines linear tracking adjustment with conventional pivot tracking, for optimum belt tracking control.
- Adjustable air belt tensioning; pivoting arm assembly.
- Includes efficient through-housing vacuum port (see page 141 for optional Vacuum Scoop Assembly).

### Variable Speed Models

- Design allows change of belt direction from forward to reverse.

**Model 64900** 600 - 4,000 SFPM, 115 V (AC)

**Model 64901** 600 - 4,000 SFPM, 230 V (AC)

**Model 64902** 2,000 - 8,000 SFPM, 230 V (AC)

**Model 64903** 2,000 - 8,000 SFPM, 460 V (AC)

### Fixed Speed Models

**Model 64904** 5,400 SFPM, 115 V (AC)

**Model 64905** 5,400 SFPM, 230 V (AC)



115 V (AC)

### Variable Speed Model


- Design allows change of belt direction from forward to reverse.

**Model 64881** 600 - 4,000 SFPM, 230 V (AC)

- This model carries the CE (European Conformity) mark, signifying that it complies with all essential requirements of relevant European health, safety and environmental protection legislation.
- Shown with optional Vacuum Scoop Assembly (see page 141).



"Pivot mount" assembly allows operator to adjust Contact Arm to any angle for peak efficiency.



230 V (AC)

Model Number	Motor hp (W)	Abrasive Belt Size Inch (mm)	Max. SFPM (SMPM)	Voltage	Phase	Frequency	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
64881	1 (744)	1/4-2 (6-51) x 72 (1,829)	600-4,000 (183-1,219)	230	1	50 Hz	120 (55)	33 (838)	22 (559)
64900	1 (744)	1/4-2 (6-51) x 72 (1,829)	600-4,000 (183-1,219)	115	1	50/60 Hz	120 (55)	33 (838)	22 (559)
64901	1 (744)	1/4-2 (6-51) x 72 (1,829)	600-4,000 (183-1,219)	230	1	50/60 Hz	120 (55)	33 (838)	22 (559)
64902	3 (2,232)	1/4-2 (6-51) x 72 (1,829)	2,000-8,000 (510-2,440)	230	3	50/60 Hz	120 (55)	33 (838)	22 (559)
64903	3 (2,232)	1/4-2 (6-51) x 72 (1,829)	2,000-8,000 (510-2,440)	460	3	50/60 Hz	120 (55)	33 (838)	22 (559)
64904	1.5 (1,116)	1/4-2 (6-51) x 72 (1,829)	5,400 (1,647)	115	1	50/60 Hz	120 (55)	33 (838)	22 (559)
64905	1.5 (1,116)	1/4-2 (6-51) x 72 (1,829)	5,400 (1,647)	230	1	50/60 Hz	120 (55)	33 (838)	22 (559)



FASTTRACK