## 142

## **Versatility Grinder Contact Arms**

Part Number	Comments	Belt Size	Contact Wheel Assembly (includes bearing and shaft)	Platen Pad
	<ul> <li>Work on broad areas</li> <li>Leave in-line scratch</li> <li>Blend spot welds</li> </ul>	1/2" x 72"	11088 5/8" dia. x 3/8" wide, rubber	11025 1/2" wide
11201	Enter channels as small as 7/16"	1/2" x 72"	11068 5/16" dia. x 3/8" wide, steel	11027 1/2" wide
11202	• Enter 5/16" x 3/4" openings	1/4" x 72"	11074 5/8" dia. x 1/8" wide, rubber	11032 1/4" wide
	<ul> <li>Grind over contact wheel or platen</li> <li>Order 11312 for heavy-duty, or 11325 for steel platen version</li> </ul>	1/2" x 72"	11078 5/8" dia. x 3/8" wide, rubber	11025 1/2" wide
11204	<ul> <li>Unique offset design</li> <li>Strap polishing is easy with this arm</li> </ul>	1/8", 1/4", 5/16" or 1/2" x 72"	11080 1" dia. x 3/8" wide, radiused rubber	None
	Order 11326 for heavy-duty steel construction version	5/8" or 3/4" x 72"	11282 3/4" dia. x 5/8" wide, rubber	11109 3/4" wide
11220, 11300, 11301, 11341	<ul> <li>Offset design and miniature contact wheels</li> <li>2" strap polish in offset area; polish turbine blades and other contours</li> </ul>	11220: 5/8" or 3/4" x 72" All Others: 1/2" x 72"	11220: 11352 5/16" x 5/8" wide, steel	None
			11300: 11332 1/4" x 3/8" wide, steel	None
			11301: 11068 5/16" x 3/8" wide, steel	None
			11341: 11342 5/16" x 3/8" wide, rubber	None
11280	<ul> <li>Grind corners, enter grooves, strap polish</li> <li>"V" shape wheel</li> </ul>	1/8" or 1/4" x 72"	11086 1" dia. x 3/8" wide, urethane, tapered	None
11286	<ul> <li>11024 Steel Platen available</li> <li>6-3/4" workable reach</li> </ul>	1/2" x 78"	11078 5/8" dia. x 3/8" wide	11025 1/2" wide
11287	<ul> <li>Grind on wheel or platen</li> <li>5-1/4" reach</li> </ul>	5/8"or 3/4" x 74-1/2"	11282 3/4" x 5/8" wide, rubber	11109 3/4" wide
11314	<ul> <li>File round openings as small as 7/16"</li> </ul>	1/4" x 72"	11066 5/16" dia. x 1/8" wide, steel	11034 1/4" wide
11320 Offset Arm	<ul> <li>For flat grinding using platen at or near corners and edges of large radius round</li> <li>Contact wheel is offset to prevent gouging</li> </ul>	1/2" x 72"	5/8" dia. x 3/8" wide, rubber	11026 1/2" wide
11321	<ul> <li>Work on contact wheel or platen pad</li> </ul>	1/2" x 72"	11070 7/16" dia. x 3/8" wide, rubber	11025 1/2" wide
11322	<ul> <li>Guide-cut</li> <li>Removes raised material within .020" or less without undercutting</li> </ul>	1/2" x 72" 60 to 80 grit	11090 5/8" dia. x 3/8" wide, rubber	None
11329	<ul> <li>Extra length arm</li> <li>17" workable reach</li> </ul>	1/2" x 98"	11078 5/8" dia. x 3/8" wide, rubber	11025 1/2" wide
11330	• Enter 1/2" x 1/2" openings	1/4" x 72"	11072 7/16" dia. x 1/8" wide, brass	11034 1/4" wide
	• Enter channels as narrow as 9/16"	1/2" x 72"	11076 7/16" dia. x 3/8" wide, steel	11027 1/2" wide