

Portable Vacuum Systems

Choose from Electric or Pneumatic Systems

Ideal for Use with Dynabrade Vacuum Air Tools

Electric Portable Vacuum System

Connect and operate two tools simultaneously

Models 61300-61311

- Choose from 9.9 (36 litres) or 17 gallon (64 litres) models. Dry vacuum only.
- Two-tool setup: two pneumatic outlets and two vacuum hose ports.
- Heavy duty stainless steel drum. Drum can be removed for special applications or locations.
- HEPA filtration (0.3 micron) with felt insert and paper bag.
- Variable vacuum control; Electronic thermal protection device prevents heat overload of motor.
- Disposable paper bag fits inside steel drum for convenient collection/disposal of debris. One disposable paper bag included with vacuum purchase. (Reorder part number 64682 for 9.9 gal. [36 L] vacuum; part number 80076 for 17 gal. [64 L] vacuum.)
- Max flow internal pneumatic workings.
- 7.5' (229 cm) water static lift/230 mbar vacuum.
- Two of the most innovative, lightweight 1-1/4" (32 mm) dia. x 20' (6 m) long coaxial hoses on the market today (see page 153).
- Auto on/off switch, 26' (8 m) electrical cord.
- UL (United States and Canada), CE (Europe), GOST (Russia) and Korean approved/listed. Also certified "M" Class Dust Collection (Europe).
- Features Dynabrade's Composite-Style Couplers and Vacuum Hose Swivel Adapter (see pages 161 and 155).



Pneumatic Portable Vacuum System

Spark-free operation

Model 64625

- Powerful industrial vacuum for commercial use, particularly where use of electric equipment is hazardous or where electric supply is not available.
- 10 gal. (37.8 litres) capacity; developed to be safe and portable.
- Top of the vacuum head is designed to work as a shelf to hold air tools, sandpaper, etc.
- The filter element is water resistant and washable.
- Includes a set of five dust bags (Part No. 64627).

Model Number	Capacity Gallon (Litres)	Voltage / Frequency	Watts	Plug (Region)	Air Pressure PSIG (Bar)	Water Static Lift Inch/cm/mbar	Sound Level	Shipping Weight lbs. (kg)	Height Inch (mm)	Width Inch (mm)
61300	9.9 (36)	120V/60 Hz	1,300	US (US/Canada)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61301	17 (64)	120V/60 Hz	1,300	US (US/Canada)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
61302	9.9 (36)	230V/50 Hz	1,400	UK (UK)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61303	17 (64)	230V/50 Hz	1,400	UK (UK)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
61304	9.9 (36)	110V/60 Hz	1,300	UK (UK)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61305	17 (64)	110V/60 Hz	1,300	UK (UK)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
61306	9.9 (36)	230V/50 Hz	1,400	CEE7/XVII (Europe)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61307	17 (64)	230V/50 Hz	1,400	CEE7/XVII (Europe)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
61308	9.9 (36)	230V/50 Hz	1,400	None (International)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61309	17 (64)	230V/50 Hz	1,400	None (International)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
61310	9.9 (36)	220V/60 Hz	1,400	(Far East)	90 (6.2)	90/229/230	76 dB(A)	48.4 (22.0)	38-1/2 (978)	20-7/8 (530)
61311	17 (64)	220V/60 Hz	1,400	(Far East)	90 (6.2)	90/229/230	76 dB(A)	61.6 (28.0)	44-7/8 (1,140)	27-5/8 (702)
64625	10 (37.8)	—	—	—	110-120 (7.6-8.3)	90/229/230	73 dB(A)	48.4 (22.0)	44 (1,118)	19 (483)