

Downdraft Sanding Tables

Eliminate Airborne Dust and Contaminants While Sanding

Standard Duty Tables

64201 - Working Area of 33" (838 mm) W x 41" (104 cm) L

64699 - Working Area of 33" (838 mm) W x 60" (152 cm) L

64700 - Working Area of 36" (914 mm) W x 72" (183 cm) L

- Ideal for use with vacuum-ready or non-vacuum tools.
- Dual filtration – accepts 1-micron pleated paper filters: 20" (508 mm) W x 25" (635 mm) L
 - Models 64201 and 64699 include two filters.
 - Model 64700 includes three filters.
- Rhino Linings® coated tabletop surface is durable and anti-slip.
- Two handy storage compartments for tools and accessories.
- 5" (127 mm) dia. casters allow easy maneuverability of table.
- Two convenient dust-tight electric outlets.
- Power source: One heavy duty electric motor, 1.0 hp.
- Electric capacity: 110 volt, 220 volt (single phase); three phase available upon request.
- Each model includes one pre-filter blanket.
- Two paper filters to choose from: 20" (508 mm) W x 25" (635 mm) L x 2" (51 mm) thick
 - 64671 Standard Paper Air Filter.
 - 64672 UL-Rated Class I Non-Flammable Air Filter (recommended when sanding bare metal).



Model 64201



Model 64700

Heavy Duty Table

64657 Working Area of 48" (122 cm) W x 96" (244 cm) L

- Up to 70% more filter area than competitive brands.
- Dual filtration – pre-filter blanket and 1-micron paper filters.
- Includes twelve paper filters
 - Eight 64658 filters: 20" (508 mm) x 25" (635 mm)
 - Four 64659 filters: 16" (406 mm) x 25" (635 mm)
- High quality reverse incline blowers. Heavy duty TEFC twin electric motors.
- Base unit is all-metal construction with CNC milled 3/4" (19 mm) MDF tabletop.
- Optional anti-static and anti-slip mat available (64970) as well as optional 5" (127 mm) diameter casters.
- Power source: Two heavy duty TEFC electric motors, 1.5 hp.
- Electric capacity: 115 volt (single phase), 208 volt (three phase), 230 volt (single phase), 230 volt (three phase); 460 volt (three phase) available upon request.



Model 64657

Model Number	Motor hp	Volts	Phase	Vacuum Suction	Sound Level	Working Area Width	Working Area Length	Height	Shipping Weight
64201	1	110/220	1	3,000 CFM	72 dB(A)	33" (838 mm)	41" (104 cm)	36" (914 mm)	275 lbs. (125 kg)
64657	1.5 (Dual)	115	1	7,000 CFM	75 dB(A)	48" (122 cm)	96" (244 cm)	37" (940 mm)	970 lbs. (440 kg)
64699	1	110/220	1	3,000 CFM	72 dB(A)	33" (838 mm)	60" (152 cm)	36" (914 mm)	285 lbs. (129 kg)
64700	1	110/220	1	3,000 CFM	72 dB(A)	36" (914 mm)	72" (183 cm)	36" (914 mm)	365 lbs. (166 kg)