

# Dynaswivel® Air Line Connectors

## Never Fight an Air Hose Again!

For use with Most Air Tools... Grinders, Sanders, Glue Guns, Staple Guns, Drills, Buffers, etc.

### THE PROBLEM



### THE SOLUTION



- The Dynaswivel® is a "universal-joint" that connects portable air tools to an air line.
- It improves tool maneuverability, minimizes operator fatigue and extends hose life.
- Patented; works great on air tools or paint guns.

### Non-Marring Composite Construction

#### Double Pivot

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.



#### Double Pivot, Flow Control

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.
- Finger-tip air-flow control dial.



| Thread Size | Part Number | Pivot  | Flow Control | Air Flow Range SCFM (LPM) | Weight oz. (kg) |
|-------------|-------------|--------|--------------|---------------------------|-----------------|
| 1/4" NPT    | 94300*      | Double | No           | up to 33 (935)            | 2.15 (0.06)     |
|             | 94407*      | Double | Yes          | up to 46 (1303)           | 2.40 (0.08)     |

### Aluminum Construction

#### Single Pivot

- Right angle "single-pivot" swivels 360° at one location.
- Designed to permit air hose to extend horizontally away from tool while allowing 360° tool maneuverability.
- Great for stationary equipment.



| Thread Size | Part Number | Flow Control | Air Flow Range SCFM (LPM) | Weight lb. (kg) |
|-------------|-------------|--------------|---------------------------|-----------------|
| 1/4" NPT    | 95590**     | No           | up to 25 (708)            | 0.11 (0.05)     |
| 3/8" NPT    | 95591**     | No           | 26-45 (736-1275)          | 0.26 (0.12)     |
| 1/2" NPT    | 95592**     | No           | 46-65 (1303-1841)         | 0.46 (0.21)     |

### Aluminum Construction

#### Double Pivot

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.



#### Double Pivot, Flow Control

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.
- Finger-tip air-flow control dial.



| Part Number                    | Thread Size | Flow Control | Air Flow Range SCFM (LPM) | Weight lb. (kg) |
|--------------------------------|-------------|--------------|---------------------------|-----------------|
| 1/8" Male x 25 1/4" NPT Female | 95852**     | No           | up to 25 (708)            | 0.18 (0.08)     |
| 1/4" NPT                       | 95460**     | No           | up to 25 (708)            | 0.20 (0.09)     |
|                                | 95734**     | Yes          | up to 25 (708)            | 0.24 (0.11)     |
| 3/8" NPT                       | 95461**     | No           | 26-45 (736-1275)          | 0.40 (0.18)     |
| 1/2" NPT                       | 95462**     | No           | 46-65 (1303-1841)         | 0.80 (0.36)     |
| 3/4" NPT                       | 95690**     | No           | above 65 (1840)           | 1.50 (0.68)     |

### Dynaswivel® Display Pak

#### Model 96177

- Includes one counter top display box and ten 94300 Dynaswivel® Air Line Fittings.



**IMPORTANT:** 150 PSIG (10.3 Bar) maximum on all models

**\*NOTE:** Do not exceed recommended torque value of 28-30 newton metres

**\*\*NOTE:** Do not use on percussion tools or in areas of high mechanical abuse