

Loop-Face Random Orbital Sanding Pads


Loop-Face Pads Accept Hookit™ II Abrasives

13,000 RPM maximum operating speed • 5/16"-24 male thread • Medium density




Loop-Face Pads

Pads accept 3M™ Hookit™ II abrasives.



Non-Vacuum Pads

High quality back-up pad. Weight-mated for smooth running and minimal tool vibration.



Vacuum Pads

Vacuum holes are precisely located to achieve proper alignment with abrasive discs for optimum vacuum capabilities.

Non-Vacuum Pads

Pad Diameter	Part Number	Holes	Thickness
5" (127 mm)	56310	0	3/8" (10 mm)
6" (152 mm)	56312	0	3/8" (10 mm)



Vacuum Pads


Pad Diameter	Part Number	Holes	Thickness
5" (127 mm)	56311	5	3/8" (10 mm)
6" (152 mm)	56313	6	3/8" (10 mm)



Rubber Random Orbital Sanding Pads


Rubber Sanding Pads for the Economy-Minded Professional

12,000 RPM maximum operating speed • 5/16"-24 male thread • Medium density




Diamond Pattern

Low-cost alternative to premium urethane pads for the economy-minded professional. Use with PSA-type abrasives.



Post Pattern

Grooves in bottom of pad allow for enhanced vacuum pick-up. No need to align vacuum holes with abrasive holes. Use with PSA-type abrasives.



Long Nap Hook-Face

Use with non-woven nylon discs.

Non-Vacuum Pads

Pad Diameter	Part Number	Face	Nap	Thickness
5" (127 mm)	50630	Diamond	—	1/2" (13 mm)
	50605	Hook	Long	1/2" (13 mm)
6" (152 mm)	50632	Diamond	—	1/2" (13 mm)
	50606	Hook	Long	1/2" (13 mm)



Vacuum Pads

Pad Diameter	Part Number	Face	Nap	Holes	Thickness
5" (127 mm)	50631	Diamond	—	5	1/2" (13 mm)
	50695	Post Pattern	—	5	1/2" (13 mm)
	50607	Hook	Long	5	1/2" (13 mm)
6" (152 mm)	50633	Diamond	—	6	1/2" (13 mm)
	50696	Post Pattern	—	6	1/2" (13 mm)
	50610	Hook	Long	6	1/2" (13 mm)

