


Hook-Face Gear-Driven Sanding Pads

Premium Urethane • Medium Density • Perfectly Weight-Mated for Dynabrade Tools


4 screw-mount system on model numbers 57306-57315 • 5 screw-mount system on model numbers 57441-58446

6 screw-mount system on original aluminum housing tool design




Hook-Face Pads

Short nap pads for use with reattachable discs.




Non-Vacuum Pads

High quality back-up pad. Weight-mated for smooth running and minimal tool vibration.



Vacuum Pads

Vacuum holes are precisely located to achieve proper alignment with abrasive discs for optimum vacuum capabilities.



Channel Vacuum Pads

3 mm (1/8") deep recessed channel. No need to align vacuum holes to pad holes.



Non-Vacuum Pads

Pad Diameter	Part Number	Max. RPM	Thickness	Screws
5" (127 mm)	57386	10,000	3/8" (10 mm)	6
	57760	12,000	3/8" (10 mm)	5
	57770	12,000	3/8" (10 mm)	4
6" (152 mm)	57773	12,000	3/8" (10 mm)	4
	57387	10,000	3/8" (10 mm)	6
	57764	12,000	3/8" (10 mm)	5
8" (203 mm)	56236	10,000	1/2" (13 mm)	5

Vacuum Pads

Pad Diameter	Part Number	Max. RPM	Thickness	Holes	Screws
6" (152 mm)	57775	12,000	3/8" (10 mm)	6	4
	57388	10,000	3/8" (10 mm)	8	6
	57765	12,000	3/8" (10 mm)	6	5
8" (203 mm)	56237	10,000	1/2" (13 mm)	8	5


Channel Vacuum Pads

Pad Diameter	Part Number	Max. RPM	Thickness	Holes	Screws
6" (152 mm)	57774	12,000	3/8" (10 mm)	8	4
	57766	12,000	3/8" (10 mm)	8	5

Wet Dynafine® Sanding Pads

3/8" (10 mm) Thick, Medium Density Pads

Pads mount with two screws



Vinyl-Face Pads

Ideal for PSA-type disc adhesion. Remove abrasive adhesive paper liner and press abrasive to vinyl-face sanding pad.



Hook-Face Pads

Short nap pads for use with reattachable discs.



Loop-Face Pads

Pads accept 3M™ Hookit™ II abrasives.



Round Non-Vacuum Pads

Pad Dimensions	Part Number	Face	Nap
2" (51 mm) Dia.	58025	Loop NEW!	—
	58030	Vinyl	—
	58031	Hook	Short
3" (76 mm) Dia.	58026	Loop NEW!	—
	58032	Vinyl	—
	58033	Hook	Short