178

ACCESSORIES

Foam-Backed Sanding Pads

Soft Density Sanding Pads



Foam Backing

Soft, dual density bonded dual action pad for use on curved and contour surfaces.



Hook-Face Pads

Short nap pads for use with reattachable discs.



Rubber-Face

For use with PSA and screen abrasives.



Non-Vacuum Pads

Pad Diameter	Part Number	MOS (RPM)	Face	Mounts with	Thickness
6" (152 mm)	50828	3,200	Rubber	5/8"-11 Female Thread	1-1/4" (32 mm)
8" (203 mm)	50829	3,200	Rubber	5/8"-11 Female Thread	1-1/4" (32 mm)
	54337	1,500	Hook	5 Screws	1" (25 mm)

NOTE: Part Number 54337 is weight-mated to Model 58445 (8" Gear-Driven Orbital Sander)

Wet/Dry Sander Disc Pads

Short Nap Hook-Face Pads

For Use With 127 mm - 203 mm Dia. Wet/Dry Sanders









Urethane

Pads are long tapered with an extremely flexible edge for sanding contours.

Rigid Backing

For finishing flat surfaces with non-woven nylon abrasive discs.

Foam Backing

Soft, dual density bonded dual action pad for use on curved and contour surfaces.

Non-Vacuum

Pad Diameter	Part Number	Туре	MOS RPM	Thread
4"-5"	50146	Rigid	6,000	1/4"-20 Female
(102-127 mm)	50147	Rigid	6,000	3/8"-24 Female
	50155	Rigid	10,000	5/8"-11 Female
5" (127 mm)	50884	Rigid	10,000	M14 x 2
	57544	Urethane	4,800	5/8"-11 Female
6" (152 mm)	50946	Foam	3,200	5/8"-11 Female
0 (132 11111)	57545	Urethane	4,800	5/8"-11 Female
7-1/4" (184 mm)	50853	Foam	3,200	5/8"-11 Female
7-1/4" (104 11111)	50854	Foam	3,200	M14 x 2
8" (203 mm)	50947	Foam	3,200	5/8"-11 Female
, ,			•	

Mini-Dynorbital® Disc Pads

Rigid and Foam Backing

- 3" (76 mm) dia. pads are compatible with angle-head and palm-style Mini-Dynorbital® sanders; Angle-Head Buffers.
- Hook-face pads accept reattachable abrasive discs as well as polishing buff pads.
- 5,000 RPM maximum.



Soft Urethane

- 3-1/2" (89 mm) pads have loop-facing to mount to rigid backing pads (P/N 50125 and P/N 50126).
- 5,000 RPM maximum.



Foam Backing

Part Number	Thread Size		
50120	1/4"-20 Female		
50122	3/8"-24 Female		

Soft Urethane

Part Number	Face
54486	Vinyl
54488	Hook



Rigid Backing

Part Number	Thread Size		
50125	1/4"-20 Female		
50126	3/8"-24 Female		

