182

ACCESSORIES

Pneumatic Wheels Inflatable Rubber Wheels

Conform to Contour of Work Surface

Dynabrade pneumatic wheels are inflatable rubber wheels designed to run on various Dynabrade tools

When fitted with an abrasive belt and inflated to the desired firmness, our pneumatic wheels are ideal for countless grinding and finishing applications.

Standard Wheels

- · For general finishing jobs.
- 1/8" thick natural, 65 durometer rubber.

Heavy Duty Wheels

- When you need a more aggressive wheel for more stock removal.
- 1/4" thick natural, 65 durometer rubber.
- Extremely durable when used properly wheel is very resistant to gouging.

Universal Arbor

Pneumatic wheels with a universal arbor include three reducer bushings (1/2", 5/8", 3/4") to greatly increase the wheel compatibility.



DynaWheel Pneumatic Wheels

For Stock and Weld Removal

Heavy Duty Wheel for Variety of Applications

DynaPump Air Pump Assembly Included with each DynaWheel and Dynacushion[®] Pneumatic Wheel



NOTE: Speed of tool must not exceed maximum operating speed of accessory

	Dimensions Diameter x Width	Part Number	Hub Composition	Arbor Hole	Wheel Part Number	Wheel Type	Belt Size Width x Length	Maximum RPM	Recommended Dynabrade Tools
O	5" x 1"	92921	Aluminum	5/8" - 11 Thread	92908	Heavy Duty	1" x 15-1/2"	4,500	10014 10500
		92922	Composite	5/8" - 11 Thread					13214, 13523
		92923	Aluminum	Universal 1/2",					
				5/8" or 3/4" Bore					1/2": 13206/507
		92924	Composite	Universal 1/2",					5/8": 13207/508
				5/8" or 3/4" Bore					3/0 . 13207/300
6	5" x 1-1/2"	92867	Aluminum	5/8"-11 Thread	92665	Heavy Duty	1-1/2" x 15-1/2"	4,500	10014 10500
		92868	Composite	5/8"-11 Thread					13214, 13523
		92928	Aluminum	Universal 1/2",					
				5/8" or 3/4" Bore					1/2": 13206/507
		92929	Composite	Universal 1/2",					5/8": 13207/508
				5/8" or 3/4" Bore					0/0 . 10201/000
C	5" x 2"	92931	Aluminum	5/8"-11 Thread	92666	Heavy Duty	2" x 15-1/2"	4,500	10014 10500
		92932	Composite	5/8"-11 Thread					13214, 13523
		92933	Aluminum	Universal 1/2",					
				5/8" or 3/4" Bore					1/2": 13206/507
		92934	Composite	Universal 1/2",					5/8": 13207/508
				5/8" or 3/4" Bore					5/0 . 15207/500



non-woven nylon belts for use on metal, wood, plastic, ceramic, fiberglass and composites. **Composite Hub**

Dynabrade pneumatic wheels support coated abrasive and

- · Molded; lightweight design.
- · Available with standard construction rubber wheels only.

Heavy Duty Aluminum Hub

- · Precision machined for balance run-out and thread quality.
- · Easily replace rubber wheel.
- · Available with both wheel construction types.

