

## ACCESSORIES

205

# Dynūba

## Cleaning and Polishing Products for Abrasive and Polishing Belts

### Dynūba 100 Ozone Safe

- Our most popular Dynūba product - extends belt life.
- Keeps belts free of metal build-up when sanding non-ferrous metals with grit 80 or finer.



| Part Name  | Part Number | Size      | Container      |
|------------|-------------|-----------|----------------|
| Dynūba 100 | 60000       | 11.25 oz  | Aerosol Can    |
|            | 60005       | 16 oz.    | Spray Bottle   |
|            | 60001       | 1 Gallon  | Can            |
|            | 60003       | 5 Gallon  | Can            |
|            | 60004       | 55 Gallon | Drum           |
| Dynūba 26  | 60020       | 1-1/2 lb. | Grease Tube    |
| Dynūba 103 | 60030       | 1/2 lb.   | Cleaning Stick |
| Dynūba 171 | 60035       | 3 lb.     | Polishing Tube |


### Dynūba 26

- Abrasive belt grease for use with all metals.
- Promotes free cutting, improves abrasive belt life; prevents heat discoloration.




### Dynūba 103

- Removes abrasive belt build-up of wood and resin residue.
- Apply to grit side of moving abrasive belts and discs.
- 8-1/2" x 1-1/2" x 1-1/2" gum rubber stick.



### Dynūba 171

- Easily cleaned.
- For brilliant cut and color on stainless and aluminum.
- Polishing compound for cloth belts and rag wheels. Apply to moving cloth belts or rag wheel.



# Lubricants and Grease

## Help Prevent Downtime

### Dynabrade Air Lube (10W/NR)

- Formulated for pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of gum/sludge for longer tool operation with greater power and less downtime.

**Part Number 95821**  
118 ml (4 oz.)

**Part Number 95842**  
473 ml (1 pt.)

**Part Number 95843**  
3.8 l (1 gallon)

**Part Number 96101**  
Display Box

- 24 - 118 ml (4 oz.) bottles



### General air tool maintenance begins with motor lubrication

Filter-lubricators, see page 162, are also necessary for greater performance and increased life of air tools. Dynabrade tools must be used with filter-lubricators to maintain all warranties.

### Gear Oil

**Part Number 95848**  
2.5 oz. (74 ml) tube

- Formulated for Dynabrade geared tools utilizing a wick-type lubrication system.
- Apply every 8 hours of operation into tool's lubrication fitting.
- Failure to lubricate will cause premature gear failure and void warranty.
- Easy to apply using with Dynabrade P/N 95541 Grease/Oil Gun (shown, sold separately).

**NOTE:** For non wick-type lubrication systems, use 95542 Gear Grease.



### Grease and Grease Gun

- Multi-purpose grease for all types of bearings, cams, gears.
- High film strength; excellent resistance to water, steam, etc.
- Workable range -18° C to 149° C (0° F to 300° F).



**Part Number 95541**  
Push-Type Grease Gun

**Part Number 95542**  
283.5 g (10 oz.) tube

- One-hand operation.