

Coated Abrasive Discs (Cont'd)

Locking-Type

DC Dynacut Zirconia Alumina

Diameter	For Use With These Dynabrade Tools		36 Grit	50 Grit	80 Grit
3" (76 mm)	3" (76 mm) Dia. Vacuum Disc Sanders		92041	92042	92043

Flap Discs Locking-Type



A/O Aluminum Oxide

Diameter	For Use With These Dynabrade Tools		40 Grit	60 Grit	80 Grit	120 Grit
2" (51 mm)	2" (51 mm) and 3" (76 mm) Dia. Disc Sanders		90970	90971	90972	90973
3" (76 mm)			90924	90925	90926	90927

3M™ Ceramic Coated Discs Roloc™

3M 3M 777F

Diameter	For Use With These Dynabrade Tools		36 Grit	50 Grit	60 Grit	80 Grit	100 Grit	120 Grit
2" (51 mm)	2" (51 mm) and 3" (76 mm) Dia. Disc Sanders		—	—	92027	92028	—	92029
3" (76 mm)			—	—	92031	92032	—	92033
4" (102 mm)	4" (102 mm) Dia. Disc Sanders		92047	—	92049	92050	—	—
4-1/2" (114 mm)	4-1/2" (114 mm) Dia. Disc Sanders		—	92052	—	92053	92054	92055

3M™ Trizact™ Abrasive Discs

3M 3M™ Trizact™

Diameter	For Use With These Dynabrade Tools	Connects to	Vacuum Type	Number of Holes	A35 Green	A10 Blue	A5 Orange
1-1/4" (19 mm)	Mini-Dynorbital® Disc Sanders	3M Hook-It™ II	Non-Vac	0	—	—	93192
11-1/4" (286 mm)	Random Orbital and Gear-Driven Sanders	3M Hook-It™ II	Non-Vac	0	91405	91406	91407