

Coated Abrasive Discs (Cont'd)

3M™ Cerium Oxide 568XA Discs

3M 3M™ Cerium Oxide 568XA

Diameter	For Use With These Dynabrade Tools	Connects to	Vacuum Type	Number of Holes	3M 568XA
11-1/4" (286 mm)	Random Orbital and Gear-Driven Sanders	3M Hook-It™ II	Non-Vac	0	91408



Scotch-Brite™ Bristle Discs

3M 3M


Length	For Use With These Dynabrade Tools	Maximum RPM	50 Grit Green	80 Grit Yellow	120 Grit White
2" (51 mm)	2" (51 mm) and 3" (76 mm) Dia. Disc Sanders	3M 25,000	92015	92016	92017
3" (76 mm)		3M 15,000	92021	92022	92023
4-1/2" (114 mm)	4-1/2" (114 mm) Dia. Disc Sanders	3M 12,000	90915	90916	90917



3M™ Clean 'n Strip™ Discs

3M 3M™ SXCRS

Length	For Use With These Dynabrade Tools	Dia.	Center Hole	Coarse
1/4" (6 mm)	Dynastraight®	4" (102 mm)	3M 1" (25 mm)	90890
1/2" (13 mm)		5" (127 mm)	3M 1" (25 mm)	90883
		6" (152 mm)	3M 1" (25 mm)	90886

Dynastraight®



Non-Woven Nylon Wheels

Abrasive Impregnated
3M Scotch-Brite™ Surface Conditioning

Length	For Use With These Dynabrade Tools	Dia.	Center Hole	Coarse	Medium
4" (102 mm)	Dynastraight®	3" (76 mm)	3M 1" (25 mm)	—	90871
6" (152 mm)	Dynisher	1" (25 mm)	A/O 1" (25 mm)	—	90866
		2" (51 mm)	A/O 1" (25 mm)	—	90865
		4" (102 mm)	A/O 1" (25 mm)	90870	90864

