

Coated Abrasive Flap Wheels

A/O Aluminum Oxide

Length	For Use With These Dynabrade Tools	Width	Wheel Thread	Center Hole	40 Grit	50 Grit	60 Grit	80 Grit	120 Grit
2-1/2" (64 mm)	Dynastraight® Flapper	 1" (25 mm)	A/O 1/4"-20 Female	—	—	—	90830	90831	—
4" (102 mm)	Dynisher	 4" (102 mm)	A/O —	3/4" (19 mm)	—	—	—	90851	—

Coated Abrasive Sanding Stars

Spindle-Mount Stars

A/O Aluminum Oxide

Diameter	For Use With These Dynabrade Tools	Shank Dia.	80 Grit	120 Grit	150 Grit	180 Grit	220 Grit	320 Grit	400 Grit
4" (102 mm)	Lightweight Dyninger 	 1/4" (6 mm)	A/O 93166	93167	93168	93169	93171	93172	93173

Arbor-Mount Stars

A/O Aluminum Oxide

Diameter	For Use With These Dynabrade Tools	Center Hole	80 Grit	120 Grit	150 Grit	180 Grit	220 Grit	320 Grit	400 Grit
4" (102 mm)	Lightweight Dyninger 	 1/2" (13 mm)	A/O 93392	93393	93394	93395	93396	93397	93398
8" (203 mm)	Dyninger 	 1" (25 mm)	A/O 93243	93245	93246	93247	93248	93251	93252

Eyelet Stars

A/O Aluminum Oxide

Diameter	For Use With These Dynabrade Tools	Center Hole	80 Grit	120 Grit	150 Grit	180 Grit	220 Grit	320 Grit	400 Grit
3/4" (19 mm)	 Lightweight Dyninger	 A/O 3-48	93579	93580	93581	93582	93583	—	—
1" (25 mm)		 A/O 3-48	93586	93587	93588	93589	93590	—	—
1-1/2" (38 mm)		 A/O 8-32	93541	93542	93543	93544	93545	93546	93547
2" (51 mm)		 A/O 1/4"-20	93551	93552	93553	93554	93555	93556	93557
3" (76 mm)		 A/O 1/4"-20	93558	93559	93560	93561	93562	93563	93564
4" (102 mm)		 A/O 1/4"-20	93565	93566	93567	93568	93569	—	—