
Reinforced Depressed Center Wheels

Type 27

A/O Aluminum Oxide

Diameter	For Use With These Dynabrade Tools	100		Center Hole	24 Grit
2" (51 mm)	2" (51 mm) Dia. Depressed Center Wheel Grinders		A/O	3/8" (10 mm)	90999
			The second second		

3M™ Green Corps™ Cut-Off Wheels





Diamond Cut-Off Wheels







Diameter	For Use With These Dynabrade Tools		Arbor	Center Hole	Wheel Thickness	Diamond Grit Wrap	Wheel Type	Part No.
3" (76 mm)	3" (76 mm) Dia. Cut-Off Wheel Tools		-	3/8" (10 mm)	3/32" (2 mm)	1/8" (3 mm)	Continuous Rim	93917
							Side Spoked	93646
4" (102 mm)	4" (102 mm) Dia. Cut-Off Wheel Tools		3/4" (19 mm)	-	3/32" (2 mm)	1/8" (3 mm)	Continuous Rim	93920
		0,					Side Spoked	93649
							Gulleted/Slotted	93661
4-1/2"	4-1/2" (114 mm) Dia.			3/8"	0/00#/0	4/01//0	0 11 1 1/01 11 1	0.404.0
(114 mm)	Cut-Off Wheel Tools		_	3/8" (10 mm)	3/32" (2 mm)	1/8" (3 mm)	Gulleted/Slotted	94912
5" (127 mm)	5" (127 mm) Dia. Cut-Off Wheel Tools	3/4" (19 mm)	-	3/32" (2 mm)	1/8" (3 mm)	Continuous Rim	93921	
						Side Spoked	93650	
						Gulleted/Slotted	93662	