

# Angle-Head Mini-Dynorbital®

## Air-Powered Random Orbital Sander

ABRASIVE  
CAPACITY
**ABRASIVE DISCS**  
 3/4" (19 mm) and  
 1-1/2" (38 mm) diameter

### Excellent for Repairing Dust Nibs on Clearcoat

- Built-in speed regulator, rear exhaust muffler, lever throttle.
- Sample 9-micron micro-finishing film discs are included.
- Optional 54585 Side Handle Assembly available.

### Model 53400 3,200 RPM

- 54028 Random Orbital Sanding Head accepts sanding pads with 1/4"-20 female thread.
- Includes 1-1/4" dia. medium density pad (54018), which has 1/4"-20 female thread and mounts to sanding head.

### Model 53401 3,200 RPM


- 54029 Random Orbital Sanding Head accepts male locking-type Roloc™ pads.
- Includes 1-1/4" dia. soft density locking-type pad (54031), which has male locking-type thread and mounts to sanding head.



Model 53400



Model 53400



**3/16" (5 mm)  
Dia. Orbit**  
 (All models on page)

Angle-Head Mini-Dynorbital® can be used  
 with Dynabrade Sanding Creme and Glaze.

### 53402 Angle-Head Versatility Kit

- Includes: 3,200 RPM air tool (not shown), 54028 Random Orbital Sanding Head, 54018 Sanding Pad, 54029 Random Orbital Sanding Head, 54031 Sanding Pad, 50107 Sanding Pad, 54021 Adapter, sample 2" dia. sanding discs, 54030 Locking-Type Rotary Sanding Head, 50055 Collet (1/4").
- Not shown: Abrasives – 3/4" and 1-1/4" dia. 9-micron (1000-grit) micro-finishing film discs; assorted wrenches.
- Tool also accepts 1/4"-28 threaded drill bits (not included).



### 53403 Sander/Buffer Versatility Kit

- Includes: 3,200 RPM air tool, 54028 Random Orbital Sanding Head, 50120 Hook 'n Loop Pad for Bonnets, 54018 Sanding Pad, 54021 Adapter, 90028 Wool Bonnet, assorted wrenches, 90027 Terry Cloth Bonnet, 95723 Finesse Sanding Creme, 95727 Dynabrade Glaze, 54017 Sanding Pad and sample abrasives.



Dynamswivel® air line connector is ideal for use with most air tools. The Dynamswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)



Model 53403

Roloc is a registered trademark of 3M Company.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
53400	.4 (298)	3,200	83 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-28 Female	1.9 (.9)	10-7/8 (276)	2-3/4 (70)
53401	.4 (298)	3,200	83 dB(A)	21 (651)	1/4 (6)	1/4" NPT	1/4"-28 Male	1.9 (.9)	10-7/8 (276)	2-3/4 (70)

Tune-Up Kit: No. 96333 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



**FASTTRACK**

Sanding Pads: Page 164 • Abrasive Discs: Page 215