

# DynaLocke®

## Air-Powered Dual-Action Sander

**ABRASIVE CAPACITY**  
**ABRASIVE DISCS**  
 3" (76 mm), 3-1/2" (89 mm),  
 5" (127 mm) and 6" (152 mm)  
 diameter

### Combination Disc Sander and Random Orbital Sander

- 12,000 RPM DynaLocke® is truly "two tools in one," easily changing from a rotary Disc Sander to Random Orbital Sander with the flip of a switch.
- Ideal for metal applications; great on composite materials. Excellent for automotive work, such as paint stripping and blending. Also utilized for leveling glue seams on Corian® and other solid surfaces.
- Switch is recessed within tool grip to prevent accidental engaging.

#### Non-Vacuum

##### Model 58460 3" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58465 3-1/2" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58430 5" Diameter


- Includes low profile, premium urethane sanding pad.

##### Model 58435 6" Diameter

- Includes low profile, premium urethane sanding pad.



**Rotary Motion**  
 For Stripping and Blending



**3/16" (5 mm) Dia. Random Orbit**  
 For Swirl-Free Finishes



#### Self-Generated Vacuum

- Self-Generated Vacuum models are ready for connection to optional portable dust collection system (see page 156).
- Tool has 1-1/4" outside diameter vacuum port, allowing increased air flow.
- Designed to vacuum in random orbital mode only.



##### Model 58461 3" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58466 3-1/2" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58431 5" Diameter

- Includes low profile, premium urethane sanding pad.

##### Model 58436 6" Diameter

- Includes low profile, premium urethane sanding pad.



DynaLocke® is ideal for leveling glue squeeze on solid surfaces.

Corian is a trademark of DuPont

| Model Number | Motor hp (W) | Motor RPM | Pad Dia. Inch (mm) | Sound Level | Maximum Air Flow SCFM (LPM) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread     | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|--------------------|-------------|-----------------------------|--------------------------|------------------|-----------------|-------------------|------------------|------------------|
| 58460        | .45 (336)    | 12,000    | 3 (76)             | 78 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.35 (1.0)        | 10-5/16 (263)    | 5-3/8 (137)      |
| 58461        | .45 (336)    | 12,000    | 3 (76)             | 78 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.35 (1.0)        | 10-5/16 (263)    | 5-3/8 (137)      |
| 58465        | .45 (336)    | 12,000    | 3-1/2 (89)         | 78 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.35 (1.0)        | 10-5/16 (263)    | 5-3/8 (137)      |
| 58466        | .45 (336)    | 12,000    | 3-1/2 (89)         | 78 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.35 (1.0)        | 10-5/16 (263)    | 5-3/8 (137)      |
| 58430        | .45 (336)    | 12,000    | 5 (127)            | 82 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.7 (1.2)         | 11-1/16 (280)    | 5-1/8 (131)      |
| 58431        | .45 (336)    | 12,000    | 5 (127)            | 82 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.6 (1.2)         | 11-1/16 (280)    | 5-1/8 (131)      |
| 58435        | .45 (336)    | 12,000    | 6 (152)            | 82 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.8 (1.3)         | 11-1/2 (293)     | 5-1/8 (131)      |
| 58436        | .45 (336)    | 12,000    | 6 (152)            | 85 dB(A)    | 23 (651)                    | 1/4 (6)                  | 1/4" NPT         | 5/16"-24 Female | 2.7 (1.2)         | 11-1/2 (293)     | 5-1/8 (131)      |

Tune-Up Kit: No. 98220 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

