


# Dynabug® “Model T” Sander

## Air-Powered Orbital Finishing Sander

<b>ABRASIVE CAPACITY</b>	<b>ABRASIVE SHEETS</b>
	4-1/2" x 5-1/2" (114 mm x 140 mm)
	4-1/4" x 4-1/2" (108 mm x 114 mm)
	<b>ABRASIVE DISCS</b>
	5", 6" (127 mm, 152 mm)

**Ideal for Featheredging, Finishing, Sanding and Blending**

- 3/32" diameter orbital action is ideal for fine finishes.
- Lightweight...only 1 lb.! Palm-style, ergonomic design features low profile grip for greater operator comfort and control.
- Operates 8-9 SCFM at 90 PSIG. Can be run by as little as 3 horsepower compressor.
- Low maintenance – easy to repair. Turbine-style vaneless air motor **needs no oil!**
- Easy interchangeable sanding pads. Uses reattachable and PSA (adhesive-backed) abrasive sheets and discs; coated and non-woven nylon.



**Orbital Motion**



Model 57920

### Non-Vacuum

#### Model 57920 4" x 4-5/16" Pad (with clips)

- Includes 57999 Vinyl-Face Pad.

#### Model 57923 4-1/4" x 4-1/2" “Quarter-Sheet” Pad

- Includes 57998 Hook-Face Pad.

#### Model 57925 4-1/4" x 4-1/2" “Quarter-Sheet” Pad

- Includes 56244 Vinyl-Face Pad.



Model 57923



Equipped with 95955 Urethane Inlet Hose


### Non-Vacuum

#### Model 57922 5" Diameter Pad

- Includes 56249 Vinyl-Face Pad.

#### Model 57924 5" Diameter Pad

- Includes 56248 Hook-Face Pad.



**Orbital Motion**



Model 57922



Equipped with 95955 Urethane Inlet Hose


### Non-Vacuum

#### Model 57926 6" Diameter Pad

- Includes 56269 Vinyl-Face Pad.

#### Model 57927 6" Diameter Pad

- Includes 56268 Hook-Face Pad.



**Orbital Motion**



Model 57926



Equipped with 95955 Urethane Inlet Hose

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57920	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.45)	5 (127)	3 (76)
57923	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5-1/2 (140)	3 (76)
57925	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5 (127)	3 (76)
57922	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5-1/2 (140)	3 (76)
57924	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5-1/2 (140)	3 (76)
57926	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5 (127)	3 (76)
57927	—	20,000	72 dB(A)	9 (255)	1/4 (6)	1/4" NPT	1 (.5)	5 (127)	3 (76)

**Tune-Up Kit: No. 96169** (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



**FASTTRACK**

Couplers/Plugs: Page 161 • Abrasive Discs and Sheets: Page 215, 220 • Sanding Pads: Page 175