## **GEAR-DRIVEN AND FINISHING SANDERS**

# **Dynabug<sup>®</sup> Orbital Sander** Air-Powered "Jitter-Bug" Type Orbital Finishing Sander

#### **ABRASIVE SHEETS** 3-2/3" x 9" (93 mm x 229 mm) 3-2/3" x 7" (93 mm x 178 mm) Also Abrasive Rolls

#### Featheredge, Finish, Sand and Blend

- 3/32" dia. orbit.
- Powerful 10.000 RPM air motor utilizes 16 SCFM at 90 PSIG.
- · Compact size and lightweight. Excellent for sanding restricted areas and vertical sides.
- Tools have heavy-duty clips to accept traditional 3-2/3" x 9" abrasive sheets (rolls also available).

#### Model 57810 Non-Vacuum

 Includes premium 57850 Vinvl-Face Sanding Pad for PSA (abrasive-backed) abrasives.



on a vertical edge.

#### Model 57811 Self-Generated Vacuum

- · Ready for connection to optional portable self-contained dust collection systems.
- Includes premium 57855 Vinyl-Face Sanding Pad for PSA (abrasive-backed) abrasives.





#### **Orbital Motion** (All models on page)



#### Model 57814 Central Vacuum

- Has 1" outside diameter vacuum port for easy central vacuum hose hook-up.
- Includes premium 57855 Vinyl-Face Sanding Pad for PSA (abrasive-backed) abrasives.





Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
.24 (179)	10,000	80 dB(A)	16 (453)	1/4 (6)	1/4" NPT	2.8 (1.3)	7-1/4 (184)	4-1/4 (108)
.24 (179)	10,000	83 dB(A)	16 (453)	1/4 (6)	1/4" NPT	2.6 (1.2)	7-1/4 (184)	4-1/4 (108)
.24 (179)	10,000	80 dB(A)	16 (453)	1/4 (6)	1/4" NPT	2.6 (1.2)	7-1/4 (184)	4-1/4 (108)
	hp (W) .24 (179) .24 (179)	hp (W) RPM   .24 (179) 10,000   .24 (179) 10,000	hp (W) RPM Level   .24 (179) 10,000 80 dB(A)   .24 (179) 10,000 83 dB(A)	hp (W) RPM Level SCFM (LPM)   .24 (179) 10,000 80 dB(A) 16 (453)   .24 (179) 10,000 83 dB(A) 16 (453)	hp (W) RPM Level SCFM (LPM) Inch (mm)   .24 (179) 10,000 80 dB(A) 16 (453) 1/4 (6)   .24 (179) 10,000 83 dB(A) 16 (453) 1/4 (6)	hp (W) RPM Level SCFM (LPM) Inch (mm) Thread   .24 (179) 10,000 80 dB(A) 16 (453) 1/4 (6) 1/4" NPT   .24 (179) 10,000 83 dB(A) 16 (453) 1/4 (6) 1/4" NPT	hp (W) RPM Level SCFM (LPM) Inch (mm) Thread Pound (kg)   .24 (179) 10,000 80 dB(A) 16 (453) 1/4 (6) 1/4" NPT 2.8 (1.3)   .24 (179) 10,000 83 dB(A) 16 (453) 1/4 (6) 1/4" NPT 2.6 (1.2)	hp (W) RPM Level SCFM (LPM) Inch (mm) Thread Pound (kg) Inch (mm)   .24 (179) 10,000 80 dB(A) 16 (453) 1/4 (6) 1/4" NPT 2.8 (1.3) 7-1/4 (184)   .24 (179) 10,000 83 dB(A) 16 (453) 1/4 (6) 1/4" NPT 2.6 (1.2) 7-1/4 (184)

Tune-Up Kit: No. 96024 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



### 69