Mini-Orbital Sander

Air-Powered Right Angle Finishing Sander

ABRASIVE DISCS 1-1/4" (32 mm) diameter

For Quick, Efficient Removal of Dust Nibs and Defects

- Ideal for use on gelcoat and clearcoat paint systems, plus finesse sanding of small areas.
- Precise 1/8" orbital action minimizes swirl marks.
- Lightweight design for operator comfort.
- · Front and rear exhaust models available.
- Each model includes 95848 Gear Oil and 95541
 Push-Type Gun, for lubricating tool gears through
 "dual wick" system. Increasing gear life extends
 the life of your tool!
- Optional safety-lock throttle lever is available (included in some regions).

Model 58037 Front Exhaust Model 58039 Rear Exhaust

 Each model runs at 12,000 RPM and includes 1-1/4" diameter rubber sanding pad (54018). Also accepts optional sanding pads 54017, 54084 and 54088 (see page 180).



Model 58038 Front Exhaust Model 58034 Rear Exhaust

 Each model runs at 12,000 RPM and includes 1-1/4" diameter locking-type foam-face sanding pad (54031).
 Also accepts optional locking-type sanding pads 54018 and 54033 (see page 180).



Model 58035 Front Exhaust

• Tool runs at 15,000 RPM and includes 1-1/4" diameter vinyl-face sanding pad (54088). Also accepts optional sanding pads 54087 and 54088 (see page 180).





58035 Mini-Orbital Sander shown with optional 95745 Speed Control.

Model Number	Exhaust	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM	Hose I.D. Size Inch (mm)	Orbit Inch (mm)	Air Inlet Thread	Weight lb (kg)	Length Inch (mm)	Height Inch (mm)
58034	Rear	.4 (298)	12,000	79	21 (595)	1/4" (6)	1/8 (3)	1/4" NPT	1.4 (0.6)	7.5 (190)	4 (102)
58035	Front	.4 (298)	15,000	85	21 (595)	1/4" (6)	1/8 (3)	1/4" NPT	1.6 (0.7)	5.4 (137)	3.8 (97)
58037	Front	.4 (298)	12,000	85	20 (566)	1/4" (6)	1/8 (3)	1/4" NPT	1.6 (0.7)	5.4 (137)	3.8 (97)
58038	Front	.4 (298)	12,000	85	20 (566)	1/4" (6)	1/8 (3)	1/4" NPT	1.6 (0.7)	5.4 (137)	4 (102)
58039	Rear	.4 (298)	12,000	79	21 (595)	1/4" (6)	1/8 (3)	1/4" NPT	1.4 (0.6)	7.5 (190)	3.8 (97)

Tune-Up Kit: No. 96179 (page 192)

