


Right Angle Wet Sander

Air-Powered Wet Rotary Sander

For Slow-Speed Polishing, Buffing and Finishing

- All models run 5", 6", or 8" diameter polishing pads. Pads sold separately.
- Accepts variety of abrasive products including WeterDry® discs, Scotch-Brite® surface conditioning discs and film-backed discs.
- Water is fed through the center of pad directly to the work surface, providing optimum flushing of work surface and pad. This prevents buildup of sanding residue on the disc, allowing the tool to be used efficiently in any position. Independent water rinse allows flushing of the work surface without starting the tool.
- Rear exhaust muffler reduces noise levels. Conventional rotary action with lubricated gears. High torque air motor has variable speed.
- Safety-lock throttle and soft-grip handle (adjusts to left or right hand).



Rotary Orbit Motion
(All models on page)



Basic Models

Model 51474 0-2,000 RPM

Model 51476 0-3,100 RPM

- Without pre-assembled hook-ups for those not requiring "through-the-tool" water feed (for those who prefer to use a hose or spray bottle).

Deluxe Model

Model 51479 0-3,100 RPM

- Includes pre-assembled hook-ups and an overhose assembly (further reduces sound level); 96323 Air Line 3/8", 95848 Gear Oil (2.5 oz. tube) and 95541 Grease Gun.



After using your wet tool, wipe the tool down with a clean, dry rag and let dry. Then store the tool with the sanding pad face down.



As 51479 is run, water is fed through pad center directly to work surface.

Scotch-Brite and WeterDry are registered trademarks of 3M Company.

Model Number	Motor hp (W)	Motor RPM	Pad Dia. Inch (mm)	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51474	.7 (522)	0-2,000	6 (152)	82 dB(A)	43 (1,218)	3/8 (10)	1/4" NPT	5/8"-11 Male	4.8 (2.2)	13 (330)	3-1/8 (79)
51476	.7 (522)	0-3,100	6 (152)	80 dB(A)	41 (1,161)	3/8 (10)	1/4" NPT	5/8"-11 Male	4.8 (2.2)	13 (330)	3-1/8 (79)
51479	.7 (522)	0-3,100	6 (152)	81 dB(A)	43 (1,218)	3/8 (10)	1/4" NPT	M14 Male	4.8 (2.2)	13 (330)	3-1/8 (79)

Tune-Up Kit: No. 96178 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Portable Wet Tank Assembly: Page 206 • Accessories: Page 159