

# Wet Dynafine®

## Air-Powered Wet Orbital Sander

ABRASIVE  
CAPACITY**ABRASIVE DISCS**2" (51 mm), 3" (76 mm)  
diameter

**Ideal for Removing Imperfections in Clearcoat and Gelcoat Paint Systems**

### Model 57902 13,000 RPM

- Features our unique "All-in-One" Misting System. The operator can spray the work surface, then remove the imperfection – all within seconds!
- "All-in-One" Misting System helps flush abrasive to achieve a consistent, repeatable finish.
- Includes 2" and 3" diameter vinyl-face sanding pads. Also accepts hook-face sanding pads, sold separately.
- Ergonomic 7° offset design for greater operator comfort and control.
- Low-vibration design allows operator to comfortably run tool for longer time periods.
- Rear exhaust directs air away from work piece; reduces sound levels.
- Insulated tool housing reduces cold air transmission to the operator.
- Gearless design means no right-angle gears to wear out. Tool life is increased!
- Includes 3' water line with 95962 Male Quick Disconnect (1/8") fitting.
- Tool also includes 94407 Flow-Control Dynaswivel®, for added maneuverability (see page 163).



Portable Wet Tank Assembly (95990) eliminates the need for a separate hose.



**Gearless**



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs (see page 162).



Model 57902



Model 57902

57902 Wet Dynafine® has "All-In-One" Misting System to wet work surface in seconds.



Model 57902

Tool accepts vinyl or hook-face sanding pads in diameters of 2" and 3" (above).

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
57902	.15 (112)	13,000	65 dB(A)	20 (566)	3/8 (10)	1/4" NPT	1.6 (0.7)	9 (229)	3-3/4 (95)

Tune-Up Kit: No. 96236 (page 192)



**FASTTRACK**

Portable Wet Tank Assembly: Page 206 • Accessories: Page 159