

3" Diameter Buffers

.4 hp, Air-Powered Buffing Tools

For Quick and Easy Spot Repair on a Variety of Surfaces

3" Diameter, .4 hp, Right Angle, Rear Exhaust

Model 53460 3,200 RPM

- Features high torque, variable speed air motor. Lubricated gears; rotary action.
- Tool comes with 50122 Hook-Face backup pad, 3" diameter.
- Includes 90027 Terry Cloth Bonnet and 90028 Wool Buffing Bonnet.

53465 Sander/Buffer Versatility Kit

- All that is needed for quick, simple spot repair on a variety of surfaces.
- Includes: Model 53417 Air Tool (3,200 RPM) with 54028 Random Orbital Sanding Head; 54021 Adapter (1/4"-28 to 1/4"-20 male); 54017 Vinyl Sanding Pad (3/4" dia.) 54018 Vinyl Sanding Pad (1-1/4" dia.); 50120 Hook-Face Pad (3" dia.); 90027 Terry Cloth Bonnet (3" dia.); 90028 Wool Buffing Pad (3" dia.); 95727 Dynabrade Glaze; 95723 Finesse Sanding Creme; 95848 Gear Oil; 95542 Grease; two 95541 Grease Guns; 95262 Wrench (14 mm); 95281 Wrench (19 mm); and sample abrasives.
- Refer to the Random Orbital Sander section (page 57) for the 53417 Mini-Dynorbital® tool specifications.



| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (LPM) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-----------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 53460 | .4 (298) | 3,200 | 81 dB(A) | 21 (595) | 1/4 (6) | 1/4" NPT | 3/8"-24 Male | 1.9 (.9) | 7 (178) | 2-3/4 (70) |

Tune-Up Kit: No. 96179 • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

3" Diameter, 7° Offset, Rear Exhaust

- 7° offset ergonomic design for control and comfort.
- High torque planetary-gear air motor; muffler reduces sound level.
- Standard rotary action.


Model 51400 3,200 RPM

Model 51401 5,000 RPM

- Includes 50126 Hook-Face Pad, 90027 Terry Cloth Bonnet and 90028 Wool Buffing Bonnet.
- 3/8"-24 Male Thread.

51405 Versatility Kit

- Includes: 51400 air tool; 3" hook-face backing pad, terry cloth bonnet, wool bonnet and foam "flat face" pad; Dynabrade Finesse-It Creme; Dynabrade Glaze and 14 mm open end wrench (not shown).



Rotary Orbital Motion

Model 51400 achieves high gloss finish when used with 95723 Dynabrade Finesse Sanding Creme and 95727 Dynabrade Glaze (each sold separately).



| Model Number | Motor hp (W) | Motor RPM | Sound Level | Maximum Air Flow SCFM (LPM) | Hose I.D. Size Inch (mm) | Air Inlet Thread | Tool Thread | Weight Pound (kg) | Length Inch (mm) | Height Inch (mm) |
|--------------|--------------|-----------|-------------|-----------------------------|--------------------------|------------------|--------------|-------------------|------------------|------------------|
| 51400 | .4 (298) | 3,200 | 80 dB(A) | 24 (680) | 3/8 (10) | 1/4" NPT | 3/8"-24 Male | 1.7 (.8) | 8-3/4 (222) | 4-1/4 (108) |
| 51401 | .4 (298) | 5,000 | 78 dB(A) | 24 (680) | 3/8 (10) | 1/4" NPT | 3/8"-24 Male | 1.7 (.8) | 8-3/4 (222) | 4-1/4 (108) |

Tune-Up Kit: No. 96174 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK