

.4 hp Die Grinders

Straight-Line, Planetary Geared, Rear Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

- Planetary gear allows tool to run at proper speed under load, maximizing life of cutting accessory.
- Extended muffler design.

Model 51200

950 RPM, 1/4" Collet

Model 51203

950 RPM, 6 mm Collet

Model 51201

3,200 RPM, 1/4" Collet

Model 51204

3,200 RPM, 6 mm Collet

Model 51202

5,000 RPM, 1/4" Collet

Model 51205

5,000 RPM, 6 mm Collet

Model 51200



Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51200 / 51203	.4 (298)	950	78 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	2.1 (1.0)	10-3/8 (264)	1-5/8 (40)
51201 / 51204	.4 (298)	3,200	77 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (0.8)	9-1/8 (232)	1-5/8 (40)
51202 / 51205	.4 (298)	5,000	80 dB(A)	23 (651)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.8 (0.8)	9-1/8 (232)	1-5/8 (40)

Tune-Up Kit: No. 96173 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

.4 hp Die Grinders

Straight-Line, Gearless, Rear Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

- Gearless motors decrease downtime and lessen repair expense when compared to geared tools.
- Collet design reduces run-out.
- Extended muffler design.

Model 52201

25,000 RPM, 1/4" Collet

Model 52231

25,000 RPM, 6 mm Collet

Model 52203

30,000 RPM, 1/4" Collet

Model 52233

30,000 RPM, 6 mm Collet

Model 52201



Dynaswivel® air line connector is ideal for use with most air tools. The Dynaswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)



Gearless

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52201 / 52231	.4 (298)	25,000	73 dB(A)	22 (623)	1/4 (6)	1/4" NPT	—	1.0 (0.5)	7-1/8 (181)	1-5/8 (41)
52203 / 52233	.4 (298)	30,000	76 dB(A)	23 (651)	1/4 (6)	1/4" NPT	—	1.0 (0.5)	7-1/8 (181)	1-5/8 (41)

Tune-Up Kit: No. 96049 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Collet Inserts: Page 94 • Carbide Burrs: Page 189 • Accessories: Page 159