

1 hp Die Grinders

Straight-Line, 6" Extension, Rear Exhaust

ABRASIVE
CAPACITY

CARBIDE BURRS, ROTARY
FILES, MOUNTED POINTS,
WHEELS AND DISCS

High Quality Air-Powered Die Grinders

Planetary Geared Models

- Governor-controlled to maintain RPM under heavy load.
- Safety-lock lever is standard on all models.
- Unique anti-clog exhaust baffling.

Model 52672

3,400 RPM, 1/4" Collet

Model 52673

4,500 RPM, 1/4" Collet

Model 52692

3,400 RPM, 6 mm Collet

Model 52693

4,500 RPM, 6 mm Collet

Model 52672



Motor Tune-Up Kits will extend the life of an air tool when used with a preventative maintenance schedule. (See page 192.)

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52672 / 52692	1 (744)	3,400	80 dB(A)	44 (1,256)	3/8 (10)	3/8" NPT	4.1 (1.9)	16-5/8 (423)	1-7/8 (48)
52673 / 52693	1 (744)	4,500	80 dB(A)	44 (1,256)	3/8 (10)	3/8" NPT	4.1 (1.9)	16-5/8 (423)	1-7/8 (48)

Tune-Up Kit: No. 96532 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Gearless Models

- Gearless for reduced maintenance and downtime.
- Governor-controlled to maintain RPM under heavy load.
- Safety-lock lever is standard on all models.
- Unique anti-clog exhaust baffling.

Model 52675

9,000 RPM, 1/4" Collet

Model 52676

12,000 RPM, 1/4" Collet

Model 52677

15,000 RPM, 1/4" Collet

Model 52678

18,000 RPM, 1/4" Collet

Model 52679

20,000 RPM, 1/4" Collet

Model 52695

9,000 RPM, 6 mm Collet

Model 52696

12,000 RPM, 6 mm Collet

Model 52697

15,000 RPM, 6 mm Collet

Model 52698

18,000 RPM, 6 mm Collet

Model 52699

20,000 RPM, 6 mm Collet

Model 52678



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs. (See page 162.)



Gearless

Model Number 1/4" / 6 mm	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52675 / 52695	1 (744)	9,000	82 dB(A)	36 (1,020)	3/8 (10)	3/8" NPT	3.2 (1.5)	14-1/4 (359)	1-7/8 (48)
52676 / 52696	1 (744)	12,000	83 dB(A)	38 (1,076)	3/8 (10)	3/8" NPT	3.2 (1.5)	14-1/4 (359)	1-7/8 (48)
52677 / 52697	1 (744)	15,000	80 dB(A)	39 (1,104)	3/8 (10)	3/8" NPT	3.3 (1.5)	15-3/8 (390)	1-7/8 (48)
52678 / 52698	1 (744)	18,000	81 dB(A)	40 (1,133)	3/8 (10)	3/8" NPT	3.3 (1.5)	15-3/8 (390)	1-7/8 (48)
52679 / 52699	1 (744)	20,000	80 dB(A)	44 (1,256)	3/8 (10)	3/8" NPT	3.3 (1.5)	15-3/8 (390)	1-7/8 (48)

Tune-Up Kit: No. 96532 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Collet Inserts: Page 94 • Carbide Burrs: Page 189 • Accessories: Page 159