

# 2" Dia. Disc Sanders

## .33 hp and .4 hp Models

### High Quality Air-Powered Disc Sanders

#### Right Angle, .33 hp, Gearless, Rear Exhaust

#### Model 52590 18,000 RPM

- Includes 51345 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter disc pads, sold separately.
- Features standard muffler for more compact design.
- Tool combines top efficiency with great value.



Model 52590

Motor Tune-Up Kits can extend the life of a tool, when used as part of a regular preventative maintenance schedule. (See page 192.)



**Gearless**

**Important:** Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52590	.33 (246)	18,000	81 dB(A)	20 (567)	1/4 (6)	1/4" NPT	3/8"-24 Male	1.9 (0.8)	4-1/2 (114)	3-7/8 (98)

**Tune-Up Kit: No. 96505** (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

#### Right Angle, .4 hp, Front Exhaust

- Includes 51344 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter pads, sold separately.
- Optional safety-lock lever available.



Model 51822

Dynaswivel® air line connector is ideal for use with most air tools. The Dynaswivel® improves tool maneuverability, minimizes operator fatigue and extends hose life. (See page 163.)

#### Model 51820 12,000 RPM

#### Model 51821 15,000 RPM

#### Model 51822 20,000 RPM

**Important:** Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51820	.4 (298)	12,000	85 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)
51821	.4 (298)	15,000	84 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)
51822	.4 (298)	20,000	87 dB(A)	3/21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	5 (134)	3-1/8 (79)

**Tune-Up Kit: No. 96179** (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

#### Right Angle, .4 hp, Rear Exhaust

- Includes 51344 Locking-Type Pad (2" diameter).
- Also accepts 3" diameter pads, sold separately.

#### Model 52520 12,000 RPM, Extended Muffler

#### Model 52521 15,000 RPM, Extended Muffler

#### Model 52522 20,000 RPM, Extended Muffler

#### Model 52540 12,000 RPM, Standard Muffler

#### Model 52541 15,000 RPM, Standard Muffler

#### Model 52542 20,000 RPM, Standard Muffler



Model 52520

Model 52520 Disc Sander offers efficient weld removal.

**Important:** Speed of tool must not exceed maximum operating speed of accessory.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52520	.4 (298)	12,000	85 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52521	.4 (298)	15,000	83 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52522	.4 (298)	20,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.2 (0.5)	7-3/8 (187)	3-1/8 (79)
52540	.4 (298)	12,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)
52541	.4 (298)	15,000	86 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)
52542	.4 (298)	20,000	87 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-20 Male	1.1 (0.5)	6 (152)	3-1/8 (79)

**Tune-Up Kit: No. 96179** (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



**FASTTRACK**