

4-1/2" Dia. Disc Sanders

.55 hp and 1.3 hp Models

ABRASIVE
CAPACITY

ABRASIVE DISCS

4" (102 mm) and
4-1/2" (114 mm) diameter

High Quality Air-Powered Disc Sanders

Light Duty Models

4-1/2" Diameter, Right Angle, .55 hp

- .55 hp models are ideal for light duty applications on metal, fiberglass and more.
- Gearless for reduced maintenance and downtime.
- Disc mount and flange nut included; 7/8" center hole abrasives are flange-mounted. Rear exhaust.
- Each model combines top efficiency with great value.

Model 52515 15,000 RPM, 5/8"-11 Thread

- Includes 50267 Disc Pad (4-1/2" diameter).

Model 52516 15,000 RPM, 5/8"-11 Thread

- Includes 50267 Disc Pad, 07184 Guard and 01462 Safety-Lock Lever.

Model 52518 15,000 RPM, M14x2 Thread

- Includes 07184 Guard and 01462 Safety-Lock Lever. (Disc Pad not included.)



The use of a filter-regulator-lubricator will increase tool performance, extend tool life and lessen repair costs. (See page 162.)



Model 52515



Gearless



Model 52515

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52515	.55 (410)	15,000	83 dB(A)	33 (934)	3/8 (10)	1/4" NPT	5/8"-11 Male	1.9 (0.8)	6 (152)	3-7/8 (98)
52516	.55 (410)	15,000	83 dB(A)	33 (934)	3/8 (10)	1/4" NPT	5/8"-11 Male	1.9 (0.8)	6 (152)	3-7/8 (98)
52518	.55 (410)	15,000	83 dB(A)	33 (934)	3/8 (10)	1/4" NPT	M14x2	1.9 (0.8)	6 (152)	3-7/8 (98)

Tune-Up Kit: No. 96522 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

4-1/2" Diameter, Right Angle, 1.3 hp

Model 51371 12,000 RPM

- Includes 51148 Disc Pad (4-1/2" diameter).
- Gearless for reduced maintenance and downtime.
- Offers higher horsepower and torque levels than similar competitive tools. Rear exhaust.
- Side handle included for comfortable operation and reduced vibration levels.
- Features spindle-lock for easy pad change.
- Tool combines top efficiency with great value.



Model 51371



Gearless

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Tool Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
51371	1.3 (969)	12,000	85 dB(A)	50 (1,416)	1/2 (13)	3/8" NPT	5/8"-11 Male	4.5 (2.0)	10-7/16 (265)	4-7/16 (112)

Tune-Up Kit: No. 96504 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK