

Depressed Center Wheel Grinders

Air-Powered Grinders, 7" Diameter

ABRASIVE
CAPACITY

**TYPE 27 REINFORCED
DEPRESSED CTR. WHEELS**
7" (178 mm) Diameter

For Fast Weld and Stock Removal, Rust and Scale Removal, Heavy Deburring

7" Diameter, Right Angle, 1.2 hp, Side Exhaust

Model 50350 6,000 RPM

- Accepts optional 7" diameter Type 27 Depressed Center Wheel, with 7/8" center hole (wheel width of 1/8" to 1/4").
- Includes 11399 Type 27 Wheel Mounting Adapter Kit, with front and rear flange plus hex wrench.
- Optional 52190 Guard is available, for left hand operation.



Model 50350

Wheel Sold Separately

7" Diameter, Right Angle, 2 hp, Side Exhaust

Model 50348 6,000 RPM

- Accepts optional 7" diameter Type 27 Depressed Center Wheel, with 7/8" center hole (wheel width of 1/8" to 1/4").
- Includes 11399 Type 27 Wheel Mounting Adapter Kit, with front and rear flange plus hex wrench.
- Powerful air motor is governor-controlled to maintain RPM under heavy load, and to insure smooth operation. Lubricated gears increase durability.
- Safety-lock throttle lever prevents accidental startup. Side handle enhances operator control. Rubber insulated grip reduces cold on operator's hand.



Model 50348

Wheel Sold Separately

7" Diameter, Vertical, 2 hp, Side Exhaust

- Each model accepts optional 7" diameter Type 27 Depressed Center Wheel, with 7/8" center hole (wheel width of 1/8" to 1/4").
- Includes 11399 Type 27 Wheel Mounting Adapter Kit, with front and rear flange plus hex wrench.

Model 52452 6,000 RPM

Model 52453 7,200 RPM

Model 52455 8,500 RPM



Always use required wheel guard. Never remove a guard that is specified for a tool.

Model 52452



Wheel Sold Separately

Important: Speed of tool must not exceed maximum operating speed of accessory. Never mount bonded grinding wheels. Always wear eye, face & body protection.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
50348	2.0 (1,491)	6,000	86 dB(A)	64 (1,812)	1/2 (13)	1/2" NPT	5/8"-11 Male	8.6 (3.9)	13-3/4 (349)	5-1/4 (132)
50350	1.2 (893)	6,000	83 dB(A)	43 (1,218)	1/2 (13)	1/2" NPT	5/8"-11 Male	6.8 (3.1)	11-3/4 (298)	4-5/8 (118)
52452	2.0 (1,491)	6,000	82 dB(A)	61 (1,728)	1/2 (13)	1/2" NPT	5/8"-11 Male	9.4 (4.2)	13 (330)	8-1/4 (210)
52453	2.0 (1,491)	7,200	84 dB(A)	66 (1,869)	1/2 (13)	1/2" NPT	5/8"-11 Male	9.4 (4.2)	13 (330)	8-1/4 (210)
52455	2.0 (1,491)	8,500	86 dB(A)	73 (2,067)	1/2 (13)	1/2" NPT	5/8"-11 Male	9.4 (4.2)	13 (330)	8-1/4 (210)

Tune-Up Kits: 50348 - No. 96043; 50350 - No. 96042; 52452-52455 - No. 96259 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)



FASTTRACK

Accessories: Page 159