Angle

Height

Drills

Air-Powered Drills, Angle Head and Right Angle

THREADED DRILL BITS & ACCESSORIES 1/4"-28 thread

Accessory

Sold Separately

Industrial-Quality Drills in a Variety of Configurations

Angle Head, .4 hp, Rear Exhaust

Model 53455 950 RPM

- Accepts 1/4"-28 threaded drill bits, sold separately.
- Angle height of only 1".
- Ideal tool for running optional 3M "SR Cutter," a plastic cutting accessory (shown). This is an efficient system for seam sealant removal, with no damage to substrate.
- Standard muffler; optional safety-lock lever available.





Model 53455



Angle Head, .4 hp, Rear Exhaust

Model 53430 3,200 RPM

- Accepts 1/4"-28 threaded drill bits, sold separately.
- Angle height of only 1".
- Extended muffler design; optional safety-lock lever available.



Right Angle, .4 hp, Rear Exhaust

Model 53435 3.200 RPM

- Accepts 1/4"-28 threaded drill bits, sold separately.
- Angle height of 2-1/4".
- Standard muffler; optional safety-lock lever available.







SR Cutter is registered trademark of 3M Company.

	Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
	53430	.4 (298)	3,200	83 dB(A)	23 (650)	1/4 (6)	1/4" NPT	1/4"-28 Female	1.9 (.9)	11-3/8 (289)	1-5/8 (40)
	53435	.4 (298)	3,200	80 dB(A)	21 (595)	1/4 (6)	1/4" NPT	1/4"-28 Female	1.9 (.9)	7 (178)	2-1/4 (57)
ı	53455	.4 (298)	950	82 dB(A)	23 (663)	1/4 (6)	1/4" NPT	1/4"-28 Female	2.1 (.9)	11-1/8 (282)	2-3/4 (70)

Tune-Up Kits: 53430 and 53455 - No. 96333; 53435 - No. 96179 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

