

Dynadie® III

Air-Powered Reciprocating Filer

ABRASIVE CAPACITY
SHANKED FILES
1/8" (3 mm) and 1/4" (6 mm) diameters

Reciprocating Filer for Precise Filing and Finishing

Model 12250 Variable-Length Stroke

- Accepts 1/4" dia. or 1/8" diameter shanked files. Files sold separately.
- Replaces tedious hand filing. Easily enters narrow slots.
- Use on metal, wood, plastic, fiberglass, etc.
- Variable-length stroke from 0-1/4". Tool runs at 5,000 strokes per minute.
- Barrel indexes 360° for ideal comfort.
- Tool includes 94407 Flow-Control Dynaswivel® (not shown).



Model Number	Motor hp (W)	Sound Level	Air Flow Rate SCFM (LPM)	Stroke Inch (mm)	Strokes Per Minute	Hose I.D. Size Inch (mm)	Air Inlet Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
12250	.2 (142)	77 dB(A)	18 (509)	0 - 1/4 (6)	5,000	3/8 (10)	1/4" NPT	1.8 (.82)	6-5/8 (170)	4-1/8 (106)

Tune-Up Kit: No. 96533 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

Files • 6" Length; 1/4" Dia. Shank

Part Number	Name	Shape	Shank	Cut
90982	Round	●	1/4" (6 mm) Dia.	"00" Very Coarse
90984	Square	■	1/4" (6 mm) Dia.	"00" Very Coarse
90989	Square	■	1/4" (6 mm) Dia.	"0" Coarse

Swiss Pattern Files • 3-1/2" - 4" Lengths; 1/8" Dia. Shank

File/Cut	Equaling	Three Square	Half Square	Round	Crochet	Round
Straight File Medium Cut 1	90900	90910	90920	90930	90940	90950
Curved File Fine Cut 2	90901	90911	90921	90931	90941	90951

Router

Air-Powered Routing Tool

ABRASIVE CAPACITY
ROUTER BITS
1/8" (3 mm) and 1/4" (6 mm) diameter shanks


Ideal for Countless Routing Applications

Model 51330 20,000 RPM, .7 hp, Front Exhaust

- Ideal for chamfers and roundover cuts on hardwoods, softwoods, solid surfaces or plastics. Great for laminate trimming, surface planing, beveling and cornering.
- Tool accepts optional high-speed steel router bits with 1/4" diameter shank capacity. Also accepts optional 1/8" collet insert, for mounting 1/8" diameter router bits.
- Lightweight, non-marring composite fixed base allows for 90° cuts. Base offers easy height adjustment.
- Safety-lock lever is standard.
- Front exhaust directs chips away from cutter.
- Spindle lock allows one-wrench cutter changing.
- Includes guide rails, ideal for use on glue seams.



Router Bit Sold Separately



Model 51331 Router Kit

- Includes 51330 Router with 93388 six-piece router bit set.

Model Number	Motor hp (W)	Motor RPM	Sound Level	Maximum Air Flow SCFM (LPM)	Hose I.D. Size Inch (mm)	Air Inlet Thread	Spindle Thread	Weight Pound (kg)	Base Size Inch (mm)	Height Inch (mm)
51330	.7 (522)	20,000	85 dB(A)	34 (963)	3/8 (10)	1/4" NPT	3/8"-24 Male	2.5 (1.1)	3-1/4 (83) x 3-1/2 (89)	8-1/4 (210)

Tune-Up Kit: 96529 (page 192) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar) • Collet Depth 1-5/8" (41 mm) • Max. Cutter Dia. 1-1/8" (29 mm)



FASTTRACK

Reciprocating Files: Page 223 • Accessories: Page 159