Dynaswivel® Air Line Connectors

Never Fight an Air Hose Again!

For use with Most Air Tools... Grinders, Sanders, Glue Guns, Staple Guns, Drills, Buffers, etc.





- The Dynaswivel® is a "universal-joint" that connects portable air tools to an air line.
- It improves tool maneuverability, minimizes operator fatigue and extends hose life.
- Patented; works great on air tools or paint guns.

Non-Marring Composite Construction

Double Pivot

 Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.

Double Pivot, Flow Control

 Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.





Thread Size	Part Number	Pivot	Flow Control	Air Flow Range SCFM (LPM)	Weight oz. (kg)
1/4" NPT	94300*	Double	No	up to 33 (935)	2.15 (0.06)
	94407*	Double	Yes	up to 46 (1303)	2.40 (0.08)

Aluminum Construction

Single Pivot

• Right angle "single-pivot" swivels 360° at one location.

 Designed to permit air hose to extend horizontally away from tool while allowing 360° tool maneuverability.

· Great for stationary equipment.

Thread Size	Part Number	Flow Control	Air Flow Range SCFM (LPM)	Weight lb. (kg)
1/4" NPT	95590**	No	up to 25 (708)	0.11 (0.05)
3/8" NPT	95591**	No	26-45 (736-1275)	0.26 (0.12)
1/2" NPT	95592**	No	46-65 (1303-1841)	0.46 (0.21)

Aluminum Construction

Double Pivot

 Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.

Double Pivot, Flow Control

• Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.

Finger-tip air-flow control dial.

Part Number	Thread Size	Flow Control	Air Flow Range SCFM (LPM)	Weight lb. (kg)	
1/8" Male x 25 1/4" NPT Female	95852**	No	up to 25 (708)	0.18 (0.08)	
1/4" NPT	95460**	No	up to 25 (708)	0.20 (0.09)	
1/4 NF1	95734**	Yes	up to 25 (708)	0.24 (0.11)	
3/8" NPT	95461**	No	26-45 (736-1275)	0.40 (0.18)	
1/2" NPT	95462**	No	46-65 (1303-1841)	0.80 (0.36)	
3/4" NPT	95690**	No	above 65 (1840)	1.50 (0.68)	

Dynaswivel® Display Pak

Model 96177

• Includes one counter top display box and ten 94300 Dynaswivel® Air Line Fittings.



IMPORTANT: 150 PSIG (10.3 Bar) maximum on all models

*NOTE: Do not exceed recommended torque value of 28-30 newton metres **NOTE: Do not use on percussion tools or in areas of high mechanical abuse