

Dynabug® "Model T" Sanding Pads

Balanced and Weight-Mated to Dynabrade Tools

All pads: 20,000 RPM max. operating speed • All pads mount with four screws (except P/N 57999 - mounts with clips)

Vinyl-Face Sanding Pads



Vinyl-Face Pads

Ideal for PSA-type disc adhesion. Remove abrasive adhesive paper liner and press abrasive to vinyl-face sanding pad. Quick disc removal.


Non-Vacuum Pads

Pad Dimensions	Part Number	Thickness	Density
5" (127 mm) Dia.	56246	5/8" (16 mm)	Soft
	56249	3/8" (10 mm)	Medium
6" (152 mm) Dia.	56269	3/8" (10 mm)	Medium
	56287	5/8" (16 mm)	Soft
4" (102 mm) W x 4-5/16" (110 mm) L with Clips	57999	1/4" (6 mm)	Medium
4-1/4" (108 mm) W x 4-1/2" (114 mm) L	56244	3/8" (10 mm)	Medium
	56245	5/8" (16 mm)	Soft

Vacuum Pads

Pad Dimensions	Part Number	Holes	Thickness	Density
4-1/4" (108 mm) W x 4-1/2" (114 mm) L	56286	6	1/4" (6 mm)	Medium
	56291	6	3/8" (10 mm)	Medium
	56293	6	5/8" (16 mm)	Soft

Hook-Face Sanding Pads



Hook-Face Pads

Short nap pads for use with reattachable discs.

Non-Vacuum Pads

Pad Dimensions	Part Number	Thickness	Density
5" (127 mm) Dia.	56247	5/8" (16 mm)	Soft
	56248	3/8" (10 mm)	Medium
6" (152 mm) Dia.	56268	3/8" (10 mm)	Medium
	56288	5/8" (16 mm)	Soft
4-1/4" (108 mm) W x 4-1/2" (114 mm) L	57996	5/8" (16 mm)	Soft
	57998	3/8" (10 mm)	Medium

Vacuum Pads


Pad Dimensions	Part Number	Holes	Thickness	Density
5" (127 mm) Dia.	58086	5	13 mm (1/2")	Medium
6" (152 mm) Dia.	58093	6	13 mm (1/2")	Medium
4-1/4" (108 mm) W x 4-1/2" (114 mm) L	56292	6	3/8" (10 mm)	Medium
	56294	6	5/8" (16 mm)	Soft
	56285	6	5 mm (3/16")	Medium



Wet Dynabug® "Model T" Sanding Pads

Hook-Face Balanced and Weight-Mated Sanding Pads

All pads: 20,000 RPM max. operating speed • All pads mount with four screws



Hook-Face Pads

Short nap pads for use with reattachable discs. Pads feature channels from vacuum holes to feed water through the sanding pad.

Vacuum Pads

Pad Dimensions	Part Number	Holes	Thickness	Density
5" (127 mm) Dia.	58086	5	13 mm (1/2")	Medium
6" (152 mm) Dia.	58093	6	13 mm (1/2")	Medium