
## **Mini-Dynorbital Sanding Heads**

Greatly Enhance the Versatility of Your Mini-Dynorbital® Sander

#### For 1/4"-20 Female Thread Pads

 Accepts 76 mm (3") and smaller diameter sanding pads with 1/4"-20 female thread.




Part Number	<b>Tool Connection</b>	Pad Connection
54028	1/4"-28 Male	1/4"-20 Male
54034	3/8"-24 Female	1/4"-20 Male
54476	1/4"-20 Female	1/4"-20 Male

#### For Male Locking-Type Thread Pads

 Accepts 76 mm (3") and smaller dia. sanding pads with male locking-type threads such as 3M Roloc.





Part Number	<b>Tool Connection</b>	Pad Connection
54029	1/4"-28 Male	Locking-Type Female Thread
54035	3/8"-24 Female	Locking-Type Female Thread
54030*	1/4"-28 Male	Locking-Type Female Thread

<sup>\*</sup> For Rotary Sanding

Roloc is a registered trademark of 3M Company

## **Mini-Dynorbital Sanding Pads**

Greatly Enhance the Versatility of Your Mini-Dynorbital® Sander

#### **Hook-Face**

- 7.500 RPM maximum.
- · For use with reattachable discs.

#### Medium, Dual Density

- 12,000 RPM maximum.
- · For wet sanding operations.

Medium, Single Density

15,000 RPM maximum.For wet sanding operations.Single density, 8 mm thick sponge.

• 6 mm thick sponge, 60 durometer rubber.

#### P/N 54090



P/N 54018



P/N 54084



P/N 54088



#### **19 mm (3/4") Dia. Sanding Pads**

Par	t Number	Max. RPM	Material	Density	Face	Thread
	54017	12,000	Foam	Medium	Rubber	1/4"-20 Female
	54085	12,000	Foam	Very Soft	Vinyl	1/4"-20 Female
	54087	15,000	Foam	Soft	Vinyl	1/4"-20 Female
	54089	7,500	Nylon	Hard	Hook	1/4"-20 Female

NOTE: To mount pads that have 1/4"-20 female thread directly to tool for conventional rotary action, use 54021 Adapter

### **32 mm (1-1/4") Dia. Sanding Pads**

<b>Part Number</b>	Max. RPM	Material	Density	Face	Thread
54018	12,000	Foam	Medium	Rubber	1/4"-20 Female
54031	12,000	Nylon	Soft	Vinyl	Locking-Type
54033	12,000	Nylon	Medium	Rubber	Locking-Type
54084	15,000	Urethane	Soft	Vinyl	1/4"-20 Female
54086	12,000	Foam	Very Soft	Vinyl	1/4"-20 Female
54088	15,000	Foam	Soft	Vinyl	1/4"-20 Female
54090	7,500	Nylon	Hard	Hook	1/4"-20 Female

NOTE: To mount pads that have 1/4"-20 female thread directly to tool for conventional rotary action, use 54021 Adapter

### Soft Density

- 15,000 RPM maximum.
- 6 mm thick sponge, vinyl-face.

# Hanger

For use with Right Angle Mini-Orbital Sanders

**Hanger Attaches to Tool for Convenient Workplace Storage** 

#### Part Number 97161

 Optional lightweight hanger easily attaches to all of Dynabrade's Right Angle Mini-Orbital Sanders.

