

Dynaflex® III Contact Arms

4" to 6-3/4" Workable Reach

Part Number		Comments	Belt Size (W x L)	Contact Wheel Assembly (includes bearing and shaft)	Platen Pad
15321		For flat grinding using platen pad	1" x 18"	15320 3/4" dia. x 7/8" wide, rubber	15323 1" wide; Soft
15326		- Allows for longer reach - Grind using platen pad	1" x 24"	15320 3/4" dia. x 7/8" wide, rubber	15323 1" wide; Soft
15350		- Reversible arm - arm can be flipped to allow for platen sanding or strap polishing - Standard with tool	1" x 18"	15349 90 durometer 2" dia. x 1" wide, rubber	15323 1" wide; Soft
15351		Reversible arm - arm can be flipped to allow for platen sanding or strap polishing	1" x 18"	15348 70 durometer 2" dia. x 1" wide, rubber	15323 1" wide; Soft
15356		Reversible arm - arm can be flipped to allow for platen sanding or strap polishing	1" x 18"	15346 40 durometer 2" dia. x 5/8" wide, rubber	15323 1" wide; Soft
15357		- Reversible arm - arm can be flipped to allow for platen sanding or strap polishing "V" shape wheel	1" x 18"	15347 2" dia. x 1" wide, rubber	15323 1" wide; Soft
15368		- Allows for longer reach - Grind using wheel surface	1" x 24"	15359 70 durometer 1" dia. x 1" wide, serrated rubber	None
15375		Great for strap polishing	1" x 24"	15348 70 durometer 2" dia. x 1" wide, rubber	None