



Roughneck® Stringer Bead Twist Wheels



Common Applications

For hard-to-reach areas

Clean prior to welding

Remove weld scale, weld spatter and corrosion



Perfect balance

Each Knot has Precisely the Same Wire Count

This fact assures perfect balance, eliminates vibration, reduces operator fatigue and increases the life of the brush.

☑ Please call for availability

Diameter	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness	Max. RPM	Steel	Stainless Steel
4" (102 mm)	.020	M10 x 1.25	32	3/16"	7/8"	7/16"	20,000	78806	☑
		M10 x 1.50						78807	☑
		3/8"-24 UNF						78808	☑
		5/8"-11 UNC						78809	78810



Knot Wire Cup Brushes



Common Applications

Heavy-duty cleaning of large metal surfaces

Cleaning prior to welding

Removal of weld scale and corrosion

☑ Please call for availability

Diameter	Wire Size	Arbor Hole	Trim Length	Maximum RPM	Steel	Stainless Steel
2-3/4" (70 mm)	.014	M10 x 1.25	1"	14,000	78815	☑
		M10 x 1.50			78816	☑
		M14 x 2.0			78817	☑
		3/8"-24 UNF			78818	☑
		5/8"-11 UNC			78819	☑
	.020	M10 x 1.25	1"	14,000	78820	☑
		M14 x 2.0			78821	☑
		5/8"-11 UNC			78822	78823